

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - FAR PART 97.23								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: ITH VOR/DME						
										CLIMBING LEFT TURN TO 3200 VIA HEADING 314 THEN DIRECT ITH VOR/DME AND HOLD.						
										ADDITIONAL FLIGHT DATA: HOLD NW, LT, 134.00 INBOUND. CHART FAS OBST: 1203 ANT ON OL MCWV TWR 422933N/0762800W CHART 3200 PRIOR TO ITH VOR/DME IN PROFILE. FAC CROSSES RWY C/L EXTENDED 2926 FROM THLD.						
1. PT <u>R</u> SIDE OF COURSE <u>314.00</u> OUTBOUND <u>2800</u> FT WITHIN <u>10</u> MILES OF <u>ITH VOR/DME</u> (IAF)														MAG VAR: 10W EPOCH YEAR: 1965		
2.																
3. FAC <u>134.00</u> FAF _____ DIST FAF TO MAP _____ THLD _____																
4. MIN. ALT <u>ESEBY/ITH 2.40 DME 1700##</u>																
8. MSA FROM: ITH VOR/DME 3700																
MINIMUMS																
TAKEOFF:		STANDARD		X		SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A		STANDARD @				
CATEGORY =====>		A			B			C			D			E		
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-14		1700	1	617	1700	1	617	1700	1 3/4	617	1700	2	617			
CIRCLING		1700	1	601	1700	1	601	1700	1 3/4	601	1780	2 1/4	681			
ESEBY FIX MINIMUMS																
S-14		1520	1	437	1520	1	437	1520	1 1/4	437	1520	1 1/2	437			
CIRCLING		1520	1	421	1560	1	461	1600	1 1/2	501	1780	2 1/4	681			
NOTES: CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ELMIRA ALTIMETER SETTING AND INCREASE ALL MDA 100 FEET AND INCREASE S-14 CATS C AND D VISIBILITY 1/4 MILE, INCREASE CIRCLING CATS C AND D 1/4 MILE, ESEBY FIX MINIMUMS INCREASE S-14 CATS C AND D VISIBILITY 1/4 MILE, AND INCREASE SEE 8260-10																
CITY AND STATE ITHACA, NY		ELEVATION: 1099 TDZE: 1083 AIRPORT NAME: ITHACA TOMPKINS REGIONAL		FACILITY IDENTIFIER: ITH		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 14, AMDT 14 11 FEB 2010				SUP VOR OR GPS RWY <div style="text-align: center;">14</div>						
										AMDT <div style="text-align: center;">13</div>						
										DATE <div style="text-align: center;">11/23/2006</div>						

**VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - FAR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.**CIRCLING CATS C AND D VISIBILITY 1/4 MILE.****CHART PROFILE NOTE: ## 1800 WHEN USING ELMIRA ALTIMETER SETTING.**

QUALITY
14
13
11/23/2006

CITY AND STATE
ITHACA, NY

ELEVATION: 1099 TDZE: 1083
AIRPORT NAME:
ITHACA TOMPKINS REGIONAL

FACILITY
IDENTIFIER:
ITH

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
VOR RWY 14, AMDT 14
11 FEB 2010

SUP: VOR OR GPS RWY
14
AMDT: 13
DATED: 11/23/2006