

PREPARED BY THE PRODUCT SUPPORT GROUP, AJV-34

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
10/17/13	MI	Escanaba	Delta County	3/4031	9/10/13	RNAV (GPS) RWY 27, Amdt 1

FDC **3/4031** ESC FI/P IAP DELTA COUNTY, ESCANABA, MI. RNAV (GPS) RWY 27, AMDT 1... CIRCLING CAT B MDA 1080/HAA 471, CAT C MDA 1280/HAA 671, CAT D MDA 1480/HAA 871. VISIBILITY CAT C 2, CAT D 2 3/4. ALTERNATE MINIMUMS STANDARD EXCEPT CAT D 900-2 3/4. DELETE NOTE WHEN VGSI INOP, CIRCLING RWY 18 NA AT NIGHT. CHANGE BARO-VNAV NA NOTE TO READ: BARO-VNAV NA WHEN USING MARQUETTE ALTIMETER SETTING. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW - 16C (4F) OR ABOVE 54C (130F). CHANGE WHEN VGSI INOP, STRAIGHT-IN/CIRCLING RWY 27 PROCEDURE NA AT NIGHT NOTE TO READ: RWY 27 STRAIGHT-IN AND CIRCLING AND CIRCLING TO RWY 18 NA AT NIGHT. CHANGE VISIBILITY REDUCTION BY HELICOPTERS NA NOTE TO READ: HELICOPTER VISIBILITY REDUCTION BELOW 1SM NOT AUTHORIZED. CHANGE REMOTE ALTIMETER SETTING NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MARQUETTE ALTIMETER SETTING AND INCREASE ALL DA 178 FT AND ALL MDA 180 FT AND INCREASE LPV ALL CATS VISIBILITY 3/8 MILE, LNAV/VNAV ALL CATS VISIBILITY 5/8 MILE, LNAV CAT C AND D VISIBILITY 3/8 MILE, AND CIRCLING CAT C VISIBILITY 1/2 MILE AND CAT D VISIBILITY 1/4 MILE. CHART CIRCLING ICON. DELETE WAAS SYMBOL. THIS IS RNAV (GPS) RWY 27, AMDT 1A.