

ILS - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.29				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		ILS: DA LOC: 3.68 MILES AFTER LUBBI LOM CLIMB TO 3800 THEN CLIMBING RIGHT TURN TO 4800 DIRECT LBB VORTAC AND HOLD (TACAN AIRCRAFT CLIMB TO 3800 THEN CLIMBING RIGHT TURN TO 5100 ON HEADING 300 AND ON LBB VORTAC R-035 TO JAZDE/LBB 5.00 DME AND HOLD NE, LT, 214.91 INBOUND), OR AS DIRECTED BY ATC. (SEE FORM 8260-10) ADDITIONAL FLIGHT DATA: HOLD NW, LT, 125.00 INBOUND. CHART IN PLANVIEW: ALTERNATE MA HOLDING, HOLD SW PLAINVIEW VOR/DME, RT, 024.00 INBOUND. CHART FAS OBST: 3296 POLE 333939N/1014704W CHART: ASR. CHART IN PLANVIEW: PLAINVIEW VOR/DME. CHART IN PLANVIEW: (CFFHF) AT 333947.31N/1013606.18W CHART IN PLANVIEW: JAZDE/LBB 5.00 DME CHART CIRCLING ICON					
LBB VORTAC		LUBBI LOM		093.78 / 9.89				5000							
PVW VOR/DME		LUBBI LOM		161.46 / 25.58				5100							
1. PT <u>L</u> SIDE OF COURSE <u>083.67</u> OUTBOUND <u>4700</u> FT WITHIN <u>15</u> MILES OF <u>LUBBI LOM</u> (IAF) 2. _____ 3. FAC: <u>263.67</u> FAF: <u>LUBBI LOM</u> DIST FAF TO MAP: <u>3.68</u> THLD: <u>3.68</u> 4. MIN. ALT: <u>LUBBI LOM 4500</u> 5. DIST TO THLD FROM OM: <u>3.68</u> MM: <u>-</u> IM: <u>-</u> 150 HAT: <u>-</u> 100 HAT: <u>-</u> GS ANT: <u>935</u> 6. MIN GS INCPT: <u>4500</u> GS ALT AT: <u>-</u> OM: <u>4477</u> MM: <u>-</u> IM: <u>-</u> 7. GS ANGLE: <u>3.00</u> TCH: <u>52.3</u> 8. MSA FROM: <u>LBB VORTAC 5300</u>										MAG VAR: 6E		EPOCH YEAR: 2020			
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		ILS: STANDARD #		LOC: STANDARD @			
CATEGORY =====>		A		B		C		D		E		F		G	
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
S-ILS 26**	3455	2400	200	3455	2400	200	3455	2400	200	3455	2400	200	3455	2400	200
S-LOC 26	3560	2400	305	3560	2400	305	3560	2400	305	3560	2400	305	3560	2400	305
CIRCLING	3720	1	438	3740	1	458	3880	1 1/2	598	3940	2	658	4100	3	818
NOTES: CHART NOTE: **RVR 1800 AUTHORIZED WITH USE OF FD OR AP OR HUD TO DA. CHART NOTE: FOR INOPERATIVE MALSR, INCREASE S-ILS 26 CAT E VISIBILITY TO RVR 4000 AND INCREASE S-LOC 26 CAT C/D/E VISIBILITY TO RVR 4500. CHART PLANVIEW NOTE: ADF OR RADAR REQUIRED.										# CAT D 700-2, CAT E 900-3 @ CAT E 900-3					
CITY AND STATE LUBBOCK, TX		ELEVATION: 3282 TDZE: 3255 AIRPORT NAME: LUBBOCK PRESTON SMITH INTL				FACILITY IDENTIFIER: I-LDT		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: ILS OR LOC RWY 26, AMDT 4B 5 JANUARY 2017				SUP: AMDT: 4A DATED 04/02/2015			

QUALITY
 6
 CHECKED

**ILS - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.29**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

MISSED APPROACH INSTRUCTIONS, (CONT.):

ALTERNATE MA: CLIMB TO 3800 THEN CLIMBING RIGHT TURN TO 5100 DIRECT PVW VOR/DME AND HOLD.

QUALITY
6
CHECKED

CITY AND STATE

LUBBOCK, TX

ELEVATION: 3282**TDZE: 3255**

AIRPORT NAME:

LUBBOCK PRESTON SMITH INTL

FACILITY
IDENTIFIER:
I-LDT

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

ILS OR LOC RWY 26, AMDT 4B

5 JANUARY 2017

SUP:

AMDT: **4A**DATED: **04/02/2015**

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

ILS STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICES - TITLE 14 CFR PART 97.29

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - KLBB

ROUTES

TRANSITION	WPT SEQ	WPT NAME	LEG TYPE	FB/FO	RNP	MAG CRS	REC NAV	ANGLE	TURN DIR	CENTER FIX	TURN RADIUS	ALTITUDE DESCRIPTION & VALUE	SPEED LIMIT DESCRIPTION & VALUE	WPT DESCRIPTION CODE
LBB	010	LBB	IF	FB										V
LBB	020	LUBBI	TF	FB								AA 05000		E
LBB	030	LUBBI	PI	FB		038.7	ILDT		R			AA 04700		EE A
PVW	010	PVW	IF	FB										V
PVW	020	LUBBI	TF	FB								AA 05100		E
PVW	030	LUBBI	PI	FB		038.7	ILDT		R			AA 04700		EE A
	010	CFFHF	IF	FB			ILDT					AA 04700 GI 04500		E I
	020	LUBBI	CF	FB		264.0	ILDT	3.00		LBB		GI 04500 GS 04477		E F
	030	RW26	CF	FO		264.0	ILDT	3.00				AT 03305		GY M
	040		CA	FB		263.7						AA 03800		M
	050	LBB	DF	FO								AA 04800		VY
	060	LBB	HM	FO		125.0			L			AA 04800		VE

POINTS

POINT NAME	LATITUDE	LONGITUDE
LBB	N334217.82	W1015450.44
PVW	N340510.29	W1014724.67
CFFHF	N333947.31	W1013606.18
LUBBI	N333945.69	W1014323.19
ILDT (LOC)	N333943.96	W1014934.35

RUNWAYS

RUNWAY	THRESHOLD LATITUDE	THRESHOLD LONGITUDE	THRESHOLD ELEVATION	PROCEDURE TCH
RW26	N333944.48	W1014747.77	03253	52.3

QUALITY
15
CHECKED

CITY AND STATE
LUBBOCK, TX

ELEVATION: 3282 TDZE: 3255
AIRPORT NAME:
LUBBOCK PRESTON SMITH INTL

FACILITY
IDENTIFIER:
I-LDT

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:
ILS OR LOC RWY 26, AMDT 4B
5 JANUARY 2017

SUP:
AMDT: 4A
DATED: 04/02/2015

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

LOC STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICES - TITLE 14 CFR PART 97.25

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - KLBB

ROUTES

TRANSITION	WPT SEQ	WPT NAME	LEG TYPE	FB/FO	RNP	MAG CRS	REC NAV	ANGLE	TURN DIR	CENTER FIX	TURN RADIUS	ALTITUDE DESCRIPTION & VALUE	SPEED LIMIT DESCRIPTION & VALUE	WPT DESCRIPTION CODE
LBB	010	LBB	IF	FB										V
LBB	020	LUBBI	TF	FB								AA 05000		E
LBB	030	LUBBI	PI	FB		038.7	ILDT		R			AA 04700		EE A
PVW	010	PVW	IF	FB										V
PVW	020	LUBBI	TF	FB								AA 05100		E
PVW	030	LUBBI	PI	FB		038.7	ILDT		R			AA 04700		EE A
	010	CFFHF	IF	FB			ILDT					AA 04700		E I
	020	LUBBI	CF	FB		264.0	ILDT			LBB		AA 04500		E F
	030	RW26	CF	FO		264.0	ILDT	3.06				AT 03305		GY M
	040		CA	FB		263.7						AA 03800		M
	050	LBB	DF	FO								AA 04800		VY
	060	LBB	HM	FO		125.0			L			AA 04800		VE

POINTS

POINT NAME	LATITUDE	LONGITUDE
LBB	N334217.82	W1015450.44
PVW	N340510.29	W1014724.67
CFFHF	N333947.31	W1013606.18
LUBBI	N333945.69	W1014323.19
ILDT (LOC)	N333943.96	W1014934.35

RUNWAYS

RUNWAY	THRESHOLD LATITUDE	THRESHOLD LONGITUDE	THRESHOLD ELEVATION	PROCEDURE TCH
RW26	N333944.48	W1014747.77	03253	52.3

QUALITY
15
CHECKED

CITY AND STATE
LUBBOCK, TX

ELEVATION: 3282 TDZE: 3255
AIRPORT NAME:
LUBBOCK PRESTON SMITH INTL

FACILITY
IDENTIFIER:
I-LDT

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:
ILS OR LOC RWY 26, AMDT 4B
5 JANUARY 2017

SUP:
AMDT: 4A
DATED: 04/02/2015