

QUALITY CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV - STANDARD

INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT.

CHART NOTE: USE MOBILE REGIONAL ALTIMETER SETTING; IF NOT RECEIVED, USE MOBILE DOWNTOWN ALTIMETER

SETTING AND INCREASE LPV DA TO 627, LNAV/VNAV DA TO 709, AND ALL MDA 20 FEET; INCREASE LNAV/VNAV

ALL CATS VISIBILITY 1/8 MILE.

CHART NOTE: CIRCLING TO RWY 26 NA AT NIGHT.

QUALITY
6
CHECKED

CITY AND STATE

BAY MINETTE, AL

ELEVATION: 248

THRE: 207

AIRPORT NAME:

BAY MINETTE MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 8, AMDT 1

5 MAY 2011

SUP:

AMDT: ORIG

DATED: 03/15/2007

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	1R8
RUNWAY	RW08
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W08A
LTP/FTP LATITUDE	305211.1625N
LTP/FTP LONGITUDE	0874941.0185W
LTP/FTP ELLIPSOIDAL HEIGHT	+00346
FPAP LATITUDE	305217.7400N
FPAP LONGITUDE	0874757.7700W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1072
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

E3F284BB

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+00629
FPAP ORTHOMETRIC HEIGHT	+00629

QUALITY
CHECKED

CITY AND STATE BAY MINETTE, AL	ELEVATION: 248 THRE: 207 AIRPORT NAME: BAY MINETTE MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 8, AMDT 1 5 MAY 2011	SUP:
				AMDT: ORIG
				DATED: 03/15/2007

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

ELEVATION: 248 THRE: 207
AIRPORT NAME:
BAY MINETTE MUNI

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 8, AMDT 1
5 MAY 2011

SUP:	
AMDT:	ORIG
DATED:	03/15/2007

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
A
Choice

CITY AND STATE BAY MINETTE, AL	ELEVATION: 248 THRE: 207 AIRPORT NAME: BAY MINETTE MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP:
			RNAV (GPS) RWY 8, AMDT 1	AMDT: ORIG
			5 MAY 2011	DATED: 03/15/2007