

<b>US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION</b>		<b>RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33</b>		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW08  CLIMB TO 3000 DIRECT SHLBE AND HOLD.  ADDITIONAL FLIGHT DATA: HOLD W, RT, 085.00 INBOUND. FAS OBST: 589 AAO 375604N/0775048W CHART HILL MOA. BUMPP TO RW08: 3.00/40 CHART: LOUISA COUNTY/FREEMAN FIELD AWOS 119.475											
RIC VORTAC	STPB (FO)	317.61 / 40.38	3000												
GVE VORTAC (IAF)	STPB (NOPT) (FB)	138.94 / 9.72	3000												
STPB (IF/IAF)	BUMPP (FB)	084.49 / 6.94	2000												
BUMPP (FAF)	RW08 (MAP) (FO)	084.58 / 5.06													
RW08 (MAP)	751 MSL	084.58													
751 MSL	SHLBE (FO)		3000												
1. PT <u>      </u> SIDE OF COURSE <u>      </u> OUTBOUND <u>      </u> FT WITHIN <u>      </u> MILES OF <u>      </u> (IAF) 2. HOLD W STPB, RT, 084.49 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAF: 084.58 FAF: BUMPP DIST FAF TO MAP: 5.06 THLD: 5.06 4. MIN. ALT: STPB 3000, BUMPP 2000 5. DIST TO THLD FROM OM: <u>      </u> MM: <u>      </u> IM: <u>      </u> 150 HAT: <u>      </u> 100 HAT: <u>      </u> GS ANT: <u>      </u> 6. MIN GS INCPT: <u>      </u> GS ALT AT: <u>      </u> OM: <u>      </u> MM: <u>      </u> IM: <u>      </u> 7. GS ANGLE: <u>      </u> TCH: 34:1 IS NOT CLEAR 8. MSA FROM: RW08 3100				MAG VAR: 10W EPOCH YEAR: 2010											
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT			ALTERNATE: N A X												
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	1360	3	1010	1360	3	1010	NA	NA	NA	NA	NA	NA	NA	NA	NA
CIRCLING	1360	3	1009	1360	3	1009	NA	NA	NA	NA	NA	NA	NA	NA	NA
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: PROCEDURE NA AT NIGHT. CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON GVE VORTAC AIRWAY RADIALS 131 CW 235. (SEE FORM 8260-10)															
CITY AND STATE  BUMPASS, VA		ELEVATION: 351 THRE: 350 AIRPORT NAME:  LAKE ANNA		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 8, ORIG  15 DEC 2011				SUP: AMDT: NONE DATED					



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
RNAV - STANDARD  
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: USE LOUISA COUNTY/FREEMAN FIELD ALTIMETER SETTING; WHEN NOT RECEIVED, PROCEDURE NA.



CITY AND STATE BUMPASS, VA	ELEVATION: 351	THRE: 350	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 8, ORIG 15 DEC 2011	SUP:
	AIRPORT NAME:				AMDT: NONE
	LAKE ANNA				DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

**PAGE 3 OF 4 PAGES**

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

ELEVATION: 351                      THRE: 350  
AIRPORT NAME:  
LAKE ANNA

**FACILITY IDENTIFIER:**  
**RNAV**

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
RNAV (GPS) RWY 8, ORIG  
15 DEC 2011

SUP:	
AMDT:	NONE
DATED:	