

<b>U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION</b> <b>VOR STANDARD INSTRUMENT APPROACH PROCEDURE</b> <b>FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23</b>								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
<b>TERMINAL ROUTES</b>										<b>MISSED APPROACH</b>						
FROM			TO			COURSE AND DISTANCE			ALTITUDE		MAP: MVC VORTAC					
											CLIMBING RIGHT TURN TO 2000 IN MVC VORTAC HOLDING PATTERN.					
ADDITIONAL FLIGHT DATA: HOLD NE, RT, 215.00 INBOUND. CHART FAS OBST: 562 TOWER 312910N/0871935W CHART A-292. FAC CROSSES RWY C/L EXTENDED 1002 FROM THLD.																
1. PT <u>  L  </u> SIDE OF COURSE <u>  035.00  </u> OUTBOUND <u>  2000  </u> FT WITHIN <u>  10  </u> MILES OF <u>  MVC VORTAC  </u> (IAF)																
2.																
3. FAC <u>  215.00  </u> FAF _____ DIST FAF TO MAP _____ THLD _____																
4. MIN. ALT <u>  FATUN/MVC 3.00 DME 1000*  </u>																
8. MSA FROM: <u>  MVC VORTAC 2000  </u>																
MAG VAR: 4E      EPOCH YEAR: 1965																
<b>MINIMUMS</b>																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		<input checked="" type="checkbox"/> X						
CATEGORY =====>		A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
S-21	1000	1	581	1000	1	581	1000	1 3/4	581	1000	1 3/4	581				
CIRCLING	1000	1	581	1000	1	581	1000	1 1/2	581	1000	2	581				
<b>FATUN FIX MINIMUMS</b>																
S-21	880	1	461	880	1	461	880	1 3/8	461	880	1 3/8	461				
CIRCLING	880	1	461	880	1	461	920	1 1/2	501	980	2	561				
NOTES: CHART NOTE: OBTAIN LOCAL ALTIMETER SETTING ON CTAF; WHEN NOT RECEIVED, USE EVERGREEN ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET AND S-21 CATS C/D VISIBILITY 1/8 MILE AND FATUN FIX MINIMUMS INCREASE S-21 CATS C/D VISIBILITY 1/8 MILE. *1060 WHEN USING EVERGREEN ALTIMETER SETTING. (SEE FORM 8260-10)																
CITY AND STATE MONROEVILLE, AL				ELEVATION: 419      THRE: 419 AIRPORT NAME:  MONROE COUNTY				FACILITY IDENTIFIER: MVC		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 21, AMDT 10 10 JANUARY 2013				SUP AMDT 9 DATE 12/20/2007		



VOR STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

## NOTES, (CONT.):

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.

CHART NOTE: RWY 21 STRAIGHT-IN AND CIRCLING AND CIRCLING RWY 03 NA AT NIGHT.



CITY AND STATE

MONROEVILLE, AL

ELEVATION: 419

THRE: 419

AIRPORT NAME:

MONROE COUNTY

FACILITY  
IDENTIFIER:  
MVC

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR RWY 21, AMDT 10

10 JANUARY 2013

SUP:

AMDT: 9

DATED: 12/20/2007