

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.							
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: 3.95 MILES AFTER MICKY INT/ZZV 10.50 DME OR AT MACUC/ZZV 14.45 DME FIX CLIMB TO 3000 THEN LEFT TURN DIRECT ZZV VOR/DME AND HOLD.					
ZZV VOR/DME (IF/IAF)		MICKY INT/ZZV 10.50 DME		088.00 / 10.50				2700		ADDITIONAL FLIGHT DATA: CHART FAS OBST: 1169 TREE 395916N/0813621W CHART: 1455 TWR 395635N/0814121W FAC CROSSES MID POINT OF RWY 04-22. CHART CIRCLING ICON					
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD W ZZV VOR/DME, RT, 088.00 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC <u>088.00</u> FAF MICKY INT/ZZV 10.50 DME <u> </u> DIST FAF TO MAP <u>3.95</u> THLD <u> </u> 4. MIN. ALT ZZV VOR/DME 3000, MICKY INT/ZZV 10.50 DME 2700, WUVAL INT/ZZV 13.00 DME 1720* 8. MSA FROM: ZZV VOR/DME 2700										MAG VAR: 6W		EPOCH YEAR:1990			
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		X			
CATEGORY ==>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
CIRCLING	1720	1 1/4	921	1720	1 1/4	921	1720	2 3/4	921		NA				
WUVAL FIX MINIMUMS (DUAL VOR RECEIVERS OR DME REQUIRED)															
CIRCLING	1480	1	681	1480	1	681	1720	2 3/4	921		NA				
NOTES: CHART NOTE: PROCEDURE NA AT NIGHT. CHART PLANVIEW NOTE: NOPT FOR ARRIVAL ON ZZV VOR/DME AIRWAY RADIALS 183 CW 347. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED USE ZANESVILLE ALTIMETER SETTING: INCREASE ALL MDA 60 FEET AND INCREASE CAT B/C VISIBILITY 1/4 MILE; WUVAL FIX MINIMUMS, INCREASE CAT C (SEE FORM 8260-10)															
CITY AND STATE		ELEVATION: 799		TDZE:		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP VOR OR GPS-A			
CAMBRIDGE, OH		AIRPORT NAME:		CAMBRIDGE MUNI		ZZV		VOR-A, AMDT 4 17 OCTOBER 2013				AMDT 3B			
												DATE 08/26/2010			

**VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):**VISIBILITY 1/4 MILE****CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1SM NOT AUTHORIZED.****CHART PROFILE NOTE: *1780 WHEN USING ZANESVILLE ALTIMETER SETTING.**

CITY AND STATE

CAMBRIDGE, OH

ELEVATION: 799

TDZE:

AIRPORT NAME:

CAMBRIDGE MUNI

FACILITY
IDENTIFIER:

ZZV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR-A, AMDT 4

17 OCTOBER 2013

SUP: VOR OR GPS-A

AMDT: 3B

DATED: 08/26/2010