

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

ILS - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.29

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	ILS: DA LOC: 5.58 MILES AFTER DINNS LOM
CRG VORTAC LIBBY INT/CRG 20.51 DME (IF/IAF)	DINNS LOM	299.61 / 16.91	2100	CLIMB TO 1000 THEN CLIMBING LEFT TURN TO 3000 ON HEADING 250 AND ON CRG VORTAC R-290 TO MONIA INT/CRG 29.18 DME/RADAR AND HOLD, OR AS DIRECTED BY ATC. ALTERNATE MA: CLIMB TO 1000 THEN CLIMBING LEFT TURN TO 3000 ON HEADING 250. EXPECT RADAR VECTORS (RADAR VECTORS).
	DINNS LOM (NOPT)	076.54 / 4.77 (I-JAX)	1900	
				ADDITIONAL FLIGHT DATA: HOLD W, LT, 110.00 INBOUND. FAS OBST: 229 AAO 302754N/0814647W CHART MAYPORT HIGH/LOW MOA.

- PT R SIDE OF COURSE 256.54 OUTBOUND 2000 FT WITHIN 15 MILES OF DINNS LOM (IAF)
-
- FAC: 076.54 FAF: DINNS LOM DIST FAF TO MAP: 5.58 THLD: 5.58
- MIN. ALT: DINNS LOM 1900
- DIST TO THLD FROM OM: 5.58 MM: - IM: 871 150 HAT: 1881 100 HAT: 924 GS ANT: 1050
- MIN GS INCPT: 1900 GS ALT AT: - OM: 1891 MM: - IM: 130
- GS ANGLE: 3.00 TCH: 51.4
- MSA FROM: JA LOM 2700

MAG VAR: 6W

EPOCH YEAR: 2010

MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		ILS: STANDARD #		LOC: STANDARD				
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
S-ILS 8	229	1800	200	229	1800	200	229	1800	200	229	1800	200	229	1800	200
S-LOC 8	480	2400	451	480	2400	451	480	4500	451	480	4500	451	480	4500	451
CIRCLING	520	1	491	520	1	491	520	1 1/2	491	640	2	611	760	2 1/2	731

NOTES:
CATEGORY II ILS SPECIAL AIRCREW AND AIRCRAFT CERTIFICATION REQUIRED S-ILS 8: CAT A, B, C, D, RA
100, RVR 1200, HATh 100, DA 129 MSL.
CATEGORY III ILS SPECIAL AIRCREW AND AIRCRAFT CERTIFICATION REQUIRED. S-ILS-8: CAT IIIa CAT
A,B,C,D, RVR 700. CAT IIIb CAT A,B,C,D, RVR 600. CAT IIIc NA.
(SEE FORM 8260-10)

CAT D 700-2, CAT E 800-2 1/2

QUALITY
1
CHECKED

CITY AND STATE JACKSONVILLE, FL	ELEVATION: 29 THRE: 29 AIRPORT NAME: JACKSONVILLE INTL	FACILITY IDENTIFIER: I-JAX	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: ILS OR LOC RWY 8, AMDT 13, 12/15/2011 ILS RWY 8 (SA CAT I), 15 DEC 2011 ILS RWY 8 (CAT II), ILS RWY 8 (CAT III)	SUP: ILS OR LOC RWY 7 AMDT: 12D DATED 04/07/2011
--	---	----------------------------------	---	--