

US DEPARTMENT OF TRANSPORTATION  
FEDERAL AVIATION ADMINISTRATION

RNAV - STANDARD  
INSTRUMENT APPROACH PROCEDURE  
TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE												
SRQ VORTAC	FAXID (FO)	140.16 / 12.82	2000	LPV: DA LNAV/VNAV: DA LNAV: RW32											
SABEE (IAF)	FAXID (NOPT) (FB)	317.66 / 14.77	2000												
FAXID (IF/IAF)	RINGY (FB)	319.45 / 6.02	1800	CLIMB TO 3000 DIRECT ACIPU AND ON TRACK 046.62 TO PAIRS AND HOLD, CONTINUE CLIMB-IN-HOLD TO 3000.											
RINGY (FAF)	ZALDI/1.50 NM TO RW32 (FB)	319.41 / 3.90													
ZALDI/1.50 NM TO RW32	RW32 (FO)	319.39 / 1.50		ADDITIONAL FLIGHT DATA: HOLD SE, LT, 336.70 INBOUND. CHART FAS OBST: 178 ANT 272207N/0823221W CHART 532 TOWER 272022N/0822754W. DISTANCE TO THLD FROM 200 HATH: 0.46 NM. WAAS CHANNEL # 72605 REFERENCE PATH ID: W32A LTP HAE: -16.3 M											
RW32 (MAP)	227 MSL	319.39													
227 MSL	ACIPU (FB)														
ACIPU	PAIRS (FO)	046.62 / 10.25	3000												
1. PT <u>      </u> SIDE OF COURSE <u>      </u> OUTBOUND <u>      </u> FT WITHIN <u>      </u> MILES OF <u>      </u> (IAF) 2. HOLD SE FAXID, RT, 319.45 INBOUND, 2000 FT. IN LIEU OF PT (IAF) 3. FAC: <u>319.41</u> FAF: <u>RINGY</u> DIST FAF TO MAP: <u>5.40</u> THLD: <u>5.40</u> 4. MIN. ALT: <u>FAXID 2000, RINGY 1800, ZALDI/1.50 NM TO RW32 540*</u> 5. DIST TO THLD FROM OM: <u>      </u> MM: <u>      </u> IM: <u>      </u> 150 HAT: <u>      </u> 100 HAT: <u>      </u> GS ANT: <u>      </u> 6. MIN GS INCPT: <u>1800</u> GS ALT AT: <u>RINGY 1800</u> OM: <u>      </u> MM: <u>      </u> IM: <u>      </u> 7. GS ANGLE: <u>3.00</u> TCH: <u>52.8</u> 34:1 IS CLEAR 8. MSA FROM: <u>RW32 2800</u>								MAG VAR: 5W		EPOCH YEAR: 2010					
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A		STANDARD							
CATEGORY =====>	A		B		C		D		E						
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	227	1/2	200	227	1/2	200	227	1/2	200	227	1/2	200			
LNAV/VNAV DA	463	1	436	463	1	436	463	1	436	463	1	436			
LNAV MDA	440	1/2	413	440	1/2	413	440	3/4	413	440	3/4	413			
CIRCLING	500	1	470	500	1	470	500	1 1/2	470	580	2	550			
NOTES: CHART NOTE: WHEN VGSJ INOP, CIRCLING RWY 4/22 NA AT NIGHT. CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 43C (109F). CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT SRQ VORTAC ON V579 NORTHBOUND. (SEE FORM 8260-10)															
CITY AND STATE		ELEVATION: 30		THRE: 27		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:			
SARASOTA/BRADENTON, FL		AIRPORT NAME:		SARASOTA/BRADENTON INTL		RNAV		RNAV (GPS) RWY 32, AMDT 3, 01/13/2011				AMDT: 2			
												DATED 09/25/2008			



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
RNAV - STANDARD  
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT SABEE ON V35 SOUTHEAST BOUND.

\*LNAV ONLY

CHART NOTE: WHEN CONTROL TOWER CLOSED, LPV AND LNAV/VNAV NA; INCREASE LNAV ALL CATS VISIBILITY TO 1 MILE.

CHART NOTE: WHEN CONTROL TOWER CLOSED, INOPERATIVE TABLE DOES NOT APPLY TO LNAV CATS A AND B.

CHART NOTE: WHEN CONTROL TOWER CLOSED, FOR INOPERATIVE MALSR, INCREASE LNAV CAT C AND D VISIBILITY TO 1 1/8 MILE.

QUALITY  
2  
CHECKED

CITY AND STATE

SARASOTA/BRADENTON, FL

ELEVATION: 30

THRE: 27

AIRPORT NAME:

SARASOTA/BRADENTON INTL

FACILITY  
IDENTIFIER:

RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 32, AMDT 3, 01/13/2011

SUP:

AMDT:

2

DATED:

09/25/2008

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**FAS DATA BLOCK INFORMATION****DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KSRQ
RUNWAY	RW32
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W32A
LTP/FTP LATITUDE	272318.8065N
LTP/FTP LONGITUDE	0823250.1060W
LTP/FTP ELLIPSOIDAL HEIGHT	-00163
FPAP LATITUDE	272421.3000N
FPAP LONGITUDE	0823401.6600W
THRESHOLD CROSSING HEIGHT (TCH)	00052.8
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	208
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0

**CRC REMAINDER**

CBACD7F4

**ADDITIONAL PATH POINT RECORD INFORMATION**

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+00081
FPAP ORTHOMETRIC HEIGHT	+00081

QUALITY  
CHECKED

CITY AND STATE

SARASOTA/BRADENTON, FL

ELEVATION: 30

THRE: 27

AIRPORT NAME:

SARASOTA/BRADENTON INTL

FACILITY  
IDENTIFIER:

RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 32, AMDT 3, 01/13/2011

SUP:

AMDT:

2

DATED:

09/25/2008

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible]

QUALITY  
8  
CHECKED

CITY AND STATE  SARASOTA/BRADENTON, FL	ELEVATION: 30	THRE: 27	FACILITY IDENTIFIER:  RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:  RNAV (GPS) RWY 32, AMDT 3, 01/13/2011	SUP:
	AIRPORT NAME:				AMDT: 2
	SARASOTA/BRADENTON INTL				DATED: 09/25/2008

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

SUSAP KSRQK7GRW32 0095003194 N27231881W082325011+0000 -0016300027115053150I

SUSAP KSRQK7PR32 RW32 001 0000W32A0N2723188065W08232501060-001630300N2724213000W08234016600106750208000528F400350CBACD7F4  
SUSAP KSRQK7PR32 RW32 002E +00081+00081LPV 72605

SUSAP KSROK7SRW32 K7PG 0 18018002825

**ELEVATION: 30                      THRE: 27**  
**AIRPORT NAME:**  
**SARASOTA/BRADENTON INTL**

FACILITY  
IDENTIFIER:  
**RNAV**

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
RNAV (GPS) RWY 32, AMDT 3, 01/13/2011

SUP:	
AMDT:	<b>2</b>
DATED:	<b>09/25/2008</b>