

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
TERMINAL ROUTES				MISSED APPROACH								
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW25 CLIMBING LEFT TURN TO 3000 DIRECT COATE AND HOLD. WHEN AUTHORIZED BY ATC, CONTINUE CLIMB-IN-HOLD TO 4000. ADDITIONAL FLIGHT DATA: HOLD NE, RT, 206.98 INBOUND. FAS OBST: 1020 AAO 410201N/0745407W								
BWZ VOR/DME	MEVNE (FB)	034.31 / 12.46	3000									
MEVNE (IAF)	IBIYU (FB)	343.96 / 5.00	3000									
SAX VORTAC (IAF)	IBIYU (FB)	282.22 / 10.77	3000									
COATE (IAF)	IBIYU (FB)	233.49 / 5.63	3000									
IBIYU (IF)	FAPAV (FB)	253.92 / 6.02	2100									
FAPAV (FAF)	RW25 (MAP) (FO)	253.85 / 5.30										
RW25 (MAP)	772 MSL	253.85										
772 MSL	COATE (FO)											
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. PROFILE STARTS AT IBIYU 3. FAC: <u>253.85</u> FAF: FAPAV DIST FAF TO MAP: <u>5.30</u> THLD: <u>5.30</u> 4. MIN. ALT: IBIYU 3000, FAPAV 2100 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u> </u> TCH: 34:1 IS NOT CLEAR 8. MSA FROM: RW25 3600												
				MAG VAR: 13W EPOCH YEAR: 1995								
MINIMUMS												
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A X								
CATEGORY =====>	A		B		C		D		E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	1260	1 1/4	889	1260	1 1/4	889	NA	NA	NA	NA	NA	NA
CIRCLING	1260	1 1/4	888	1300	1 1/4	928	NA	NA	NA	NA	NA	NA
LEHIGH VALLEY INTL ALTIMETER SETTING MINIMUMS												
LNAV MDA	1540	1 1/4	1169	1540	1 1/2	1169	NA	NA	NA	NA	NA	NA
CIRCLING	1540	1 1/4	1168	1600	1 1/2	1228	NA	NA	NA	NA	NA	NA
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: PROCEDURE NA AT NIGHT. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON SAX VORTAC AIRWAY RADIALS 209 CW 311. CHART NOTE: OBTAIN LOCAL ALTIMETER SETTING ON CTAF; WHEN NOT RECEIVED, USE LEHIGH VALLEY INTL (SEE FORM 8260-10)												
CITY AND STATE		ELEVATION: 372 TDZE: 371		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:			SUP:			
BLAIRSTOWN, NJ		AIRPORT NAME: BLAIRSTOWN				RNAV (GPS) RWY 25, AMDT 2A 20 AUGUST 2015			AMDT: 2			
									DATED 02/09/2012			

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

ALTIMETER SETTING.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT COATE ON T218, V116-188 SOUTHEAST BOUND AND V252 NORTHBOUND.

CHART PROFILE NOTE: DESCENT ANGLE NA.

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.

CITY AND STATE
BLAIRSTOWN, NJ

ELEVATION: 372 TDZE: 371
AIRPORT NAME:
BLAIRSTOWN

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 25, AMDT 2A
20 AUGUST 2015

SUP: 4
AMDT: CHECKED
DATED: 02/09/2012

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

CITY AND STATE BLAIRSTOWN, NJ	ELEVATION: 372 AIRPORT NAME: BLAIRSTOWN	TDZE: 371 RNAV	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 25, AMDT 2A 20 AUGUST 2015	SUP: 4
					AMDT: 2
					DATED: 02/09/2012

SUSAP 1N7 K6SRW25 K6PG018018003625M

CITY AND STATE BLAIRSTOWN, NJ	ELEVATION: 372	TDZE: 371	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 25, AMDT 2A 20 AUGUST 2015	SUP: <div>QUALITY 4</div>
	AIRPORT NAME: BLAIRSTOWN	AMDT: <div>CHECKED 2</div>			
	DATED: 02/09/2012				

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICES - TITLE 14 CFR PART 97.33								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.				
ARINC SUMMARY - 424-18 - RNAV (GPS)												
ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	BWZ	BWZ	010		IF		FB					
	BWZ	MEVNE	020	IAF	TF		FB	2.0	034.3 (021.3T)	012.5	AA 03000	
	BWZ	IBIYU	030		TF		FB	1.0	344.0 (331.0T)	005.0	AA 03000	
	COATE	COATE	010	IAF	IF		FB					
	COATE	IBIYU	020		TF		FB	1.0	233.5 (220.5T)	005.6	AA 03000	
	SAX	SAX	010	IAF	IF		FB					
	SAX	IBIYU	020		TF		FB	1.0	282.2 (269.2T)	010.8	AA 03000	
		IBIYU	010	FACF	IF		FB				AA 03000	
		FAPAV	020	FAF	TF		FB	0.5	253.9 (240.9T)	006.0	AA 02100	
		RW25	030	MAP	TF		FO	0.3	253.9 (240.9T)	005.3	AT 01260	
MISSED APPROACH		FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
			040		CA		FB		253.9 (240.9T)		AA 00772	
		COATE	050		DF	L	FO				AA 03000	
		COATE	060		HM	R	FO		207.0 (194.0T)	004.0	AA 03000	
POINT DATA		WAYPOINT	LAT IN SECS		LONG IN SECS		LAT IN MINS		LONG IN MINS			
		BWZ	N404754.36		W0744918.60		N4047.906		W07449.310			
		SAX	N410403.16		W0743217.93		N4104.053		W07432.299			
		COATE	N410810.42		W0744142.60		N4108.174		W07441.710			
		FAPAV	N410057.74		W0745329.04		N4100.962		W07453.484			
		IBIYU	N410353.47		W0744632.32		N4103.891		W07446.539			
		MEVNE	N405931.09		W0744319.77		N4059.518		W07443.330			
		RW25	N405822.45		W0745935.98		N4058.374		W07459.600			
RUNWAY DATA		RWY	THRESHOLD ELEVATION		TCH							
		RW25	00371		50							

CITY AND STATE BLAIRSTOWN, NJ	ELEVATION: 372 AIRPORT NAME: BLAIRSTOWN	TDZE: 371	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 25, AMDT 2A 20 AUGUST 2015	SUP: AMDT: DATED: 02/09/2012
	<div style="color: green; font-weight: bold; text-align: right;"> QUALITY 4 CHECKED 2 </div>				