

PREPARED BY THE PRODUCT SUPPORT GROUP, AJV-34

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
7-Feb-13	NY	Schenectady	Schenectady County	2/2335	12/14/12	RNAV (GPS) RWY 22, Orig

FDC **2/2335** SCH FI/P IAP SCHENECTADY COUNTY, SCHENECTADY, NY. RNAV (GPS) RWY 22, ORIG... LNAV MDA 900/HATH 522 ALL CATS. VIS CAT C/D 1 1/2. CIRCLING CATS A/B/C MDA 900/HAA 522. CHART VDP AT 1.48 MILES TO RW22*. DELETE NOTE: WHEN VGSI INOP, STRAIGHT-IN/CIRCLING RWY 22 PROCEDURE NA AT NIGHT. CHART NOTE: CIRCLING TO RWY 15 AND 33 NA AT NIGHT. CHANGE LOCAL ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ALBANY ALTIMETER SETTING AND INCREASE LPV DA TO 661, LNAV/VNAV DA TO 749, AND ALL MDA 40 FEET, INCREASE LPV AND LNAV/VNAV ALL CATS, LNAV CAT C AND D AND CIRCLING CAT C VISIBILITY 1/8 MILE. CHANGE FOR UNCOMPENSATED BARO-VNAV SYSTEMS NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW - 15C (5F) OR ABOVE 54C (130F). CHANGE PROCEDURE NA FOR ARRIVALS PLANVIEW NOTE TO READ: PROCEDURE NA FOR ARRIVAL ON CAM VOR/DME AIRWAY RADIALS 203 CW 016. THIS IS RNAV (GPS) RWY 22, ORIG-A.