

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION LOC STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - FAR PART 97.25								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH							
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: 4.30 MILES AFTER STOG LOM/I-OWD 5.08 DME OR AT I-OWD 0.78 DME FIX CLIMBING LEFT TURN TO 3000 VIA BOS VOR/DME R-240 TO MILIS INT/BOS 20.86 DME AND HOLD. CONTINUE CLIMB-IN-HOLD TO 3000; OR WHEN DIRECTED BY ATC, CLIMBING LEFT TURN VIA HEADING 270 AND GDM VOR/DME R-135 TO WHYBE INT AND HOLD SE, RT, 315.34 INBOUND. ADDITIONAL FLIGHT DATA: HOLD NE, RT, 239.80 INBOUND. CHART FAS OBST: 319 TREE 420820N/0710840W 459 AAO 420713N/0710840W. CHART 198 TREE 420957N/0710917W. CHART IN PLANVIEW: WHYBE INT. STOG TO RW35: 2.87/40. DO NOT CHART ALTERNATE MA HOLDING AT WHYBE.							
PVD VORTAC (IAF)		CURLI INT/I-OWD 11.95 DME (NOPT)		057.00 / 23.91				2200									
CURLI INT/I-OWD 11.95 DME (IF)		STOG LOM/I-OWD 5.08 DME (NOPT)		349.77 / 6.87 (I-OWD)				1400									
1. PT <u>R</u> SIDE OF COURSE <u>169.77</u> OUTBOUND <u>2100</u> FT WITHIN <u>10</u> MILES OF <u>STOG LOM</u> (IAF) 2. _____ 3. FAC <u>349.77</u> FAF <u>STOG LOM/I-OWD 5.08 DME</u> DIST FAF TO MAP <u>4.30</u> THLD <u>4.30</u> 4. MIN. ALT <u>STOG LOM 1400, DIKEY/2.48 DME 580</u> 8. MSA FROM: <u>OW LOM 100-190 1900, 190-100 2500</u>														MAG VAR: 15W		EPOCH YEAR: 1980	
MINIMUMS																	
TAKEOFF:		STANDARD		X		SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N/A		STANDARD @					
CATEGORY =====>		A			B			C			D			E			
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA		
S-35	580	3/4	531	580	3/4	531	580	1 1/2	531	580	1 3/4	531					
CIRCLING	600	1	551	600	1	551	640	1 1/2	591	680	2	631					
DIKEY FIX MINIMUMS																	
S-35	500	3/4	451	500	3/4	451	500	1 1/4	451	500	1 1/2	451					
CIRCLING	600	1	551	600	1	551	640	1 1/2	591	680	2	631					
NOTES: CHART NOTE: CIRCLING TO RWY 10/28 NA AT NIGHT. @ NA WHEN CONTROL TOWER CLOSED. CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY TO CAT C. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT PVD VORTAC VIA V139-151 WESTBOUND.																	
CITY AND STATE NORWOOD, MA				ELEVATION: 49 TDZE: 49 AIRPORT NAME: NORWOOD MEMORIAL				FACILITY IDENTIFIER: I-OWD		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: LOC RWY 35, AMDT 10A 07 MAY 2009				SUP AMDT 10 DATE 07/05/2007			

 QUALITY
CHECKED