

PAGE 1 OF 4 PAGES

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

INCREASE ALL MDA 100 FEET. INCREASE LP CAT C VISIBILITY 1/4 MILE, LNAV CAT C VISIBILITY 1 MILE, AND CIRCLING CAT C VISIBILITY 1/2 MILE.

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1SM NOT AUTHORIZED.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT MSN VORTAC ON AIRWAY RADIALS 282 CW 031.

CHART PROFILE NOTE: DESCENT ANGLE NA.

CHART NOTE: CIRCLING NA TO RWY 14-32.

QUALITY
A
CHECKED

CITY AND STATE BARABOO, WI	ELEVATION: 979	THRE: 967	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 19, AMDT 1 25 JULY 2013	SUP:
	AIRPORT NAME:				AMDT: ORIG
	BARABOO WISCONSIN DELLS				DATED: 08/30/2007