

RNAV (GPS) - STANDARD INSTRUMENT APPROACH PROCEDURE FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: HAXEM											
PVD VORTAC (IF/AF)	FEKWU (FB)	164.96 / 8.00	1800	CLIMB TO 2100 DIRECT RUBLE AND VIA 169.02 TRACK TO NICOD AND HOLD.											
				ADDITIONAL FLIGHT DATA: HOLD N, RT, 165.00 INBOUND. CHART FAS OBST: 349 AAO 413618N/0711850W FEKWU TO RW16: 3.04/40 FAC CROSSES RWY C/L EXTENDED 3000 FROM THLD.											
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF)				MAG VAR: 15W EPOCH YEAR: 1995											
2. HOLD N PVD VORTAC, RT, 164.96 INBOUND, 3000 FT. IN LIEU OF PT (IAF)															
3. FAC: <u>165.73</u> FAF: <u>FEKWU</u> DIST FAF TO MAP: <u>4.51</u> THLD: <u>5.00</u>															
4. MIN. ALT: <u>PVD VORTAC 3000, FEKWU 1800</u>															
5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u>															
6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u>															
7. GS ANGLE: <u> </u> TCH: <u>34:1 IS NOT CLEAR</u>															
8. MSA FROM: <u>HAXEM 2200</u>															
MINIMUMS															
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	STANDARD @										
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	600	1	438	600	1	438	600	1 1/4	438		NA				
CIRCLING	700	1	528	700	1	528	700	1 1/2	528		NA				
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART PLANVIEW NOTE: NOPT FOR ARRIVAL ON PVD VORTAC AIRWAY RADIALS 234 CW 093. CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT. SEE 8260-10															
CITY AND STATE NEWPORT, RI		ELEVATION: 172 TDZE: 162 AIRPORT NAME: NEWPORT STATE		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 16, ORIG				SUP: AMDT: NONE DATED					

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE PROVIDENCE ALTIMETER SETTING AND INCREASE ALL MDAS 60 FEET.

CHART NOTE: VDP NA WITH PROVIDENCE ALTIMETER SETTING.

CITY AND STATE

NEWPORT, RI

ELEVATION: 172 TDZE: 162

AIRPORT NAME:

NEWPORT STATE

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 16, ORIG

APR 10 2008

SUP:

AMDT: NONE

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

CITY AND STATE NEWPORT, RI	ELEVATION: 172 TDZE: 162 AIRPORT NAME: NEWPORT STATE	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 16, ORIG APR 10 2008	SUP:
				AMDT: NONE
				DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-15

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE
	PVD	PVD	010		HF	R	FB		165.0(150T)	004.0	03000
		PVD	010	FACF	IF		FB				
		FEKWU	020	FAF	TF		FB	0.5	165.0(150T)	008.0	01800
		HAXEM	030	MAP	TF		FO	0.3	165.7(151T)	004.5	00186

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE
		040		CA		FB	1.0	165.7(151T)		00572
	RUBLE	050		DF		FB	1.0			
	NICOD	060		TF		FO	1.0	169.0(154T)		02100
	NICOD	070		HM	R	FO	2.0	165.0(150T)	004.0	02100

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	PVD	N414327.64	W0712546.70	N4143.461	W07125.778
	FEKWU	N413631.76	W0712026.35	N4136.529	W07120.439
	HAXEM	N413235.54	W0711730.13	N4132.592	W07117.502
	NICOD	N412436.38	W0711154.39	N4124.606	W07111.907
	RUBLE	N412813.66	W0711415.01	N4128.228	W07114.250
	RW16	N413211.70	W0711706.69	N4132.195	W07117.112

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW16	00146	40

CITY AND STATE
NEWPORT, RI

ELEVATION: 172 TDZE: 162
 AIRPORT NAME:
 NEWPORT STATE

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 16, ORIG

SUP:
AMDT: NONE
DATED:

APR 10 2009