

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

| AIRAC DATE | STATE | CITY | AIRPORT | FDC NUMBER | FDC DATE | SUBJECT |
|---------------|-------|-----------|-----------|---------------|-------------|----------------------------|
| 25-Jun-15 | FL | Crestview | Bob Sikes | 5/3455 | 04/30/15 | RNAV (GPS) RWY 17, Orig |

EFFECTIVE 25-JUN-2015

FDC **5/3455** CEW IAP BOB SIKES, CRESTVIEW, FL. RNAV (GPS) RWY 17, ORIG... CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON CEW VORTAC AIRWAY RADIALS 358 CW 088. CHANGE ALTIMETER SETTING NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE EGLIN AFB ALTIMETER SETTING AND INCREASE ALL DA/MDA 60 FEET. DELETE PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT. CHANGE BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 54C (130F). THIS IS RNAV (GPS) RWY 17 ORIG-A. 1504281823-PERM