

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	QITEJ CLIMBING LEFT TURN TO 5600 DIRECT LIQED AND HOLD, CONTINUE CLIMB-IN-HOLD TO 5600. ADDITIONAL FLIGHT DATA: HOLD N, RT, 194.36 INBOUND. FAS OBST: 1359 AAO 442828N/0723920W CHART 4500 BLOCK 5000 AT POESY. CHART MANDATORY 3400 AT RIFTS. CHART MANDATORY 3400 AT SLAGS. CHART 3100 BLOCK 3400 AT NUNOE. FAC CROSSES MIDPOINT OF RWY 1-19. CHART CIRCLING ICON.											
MPV VOR/DME	POESY (TF) (FB) (RNP 2.00)	338.22 / 12.23	4500												
POESY (IAF)	RIFTS (TF) (FB) (RNP 1.00)	323.23 / 5.67	3400												
RIFTS (IF)	SLAGS (TF) (FB) (RNP 1.00)	011.10 / 3.76	3400												
SLAGS	NUNOE (TF) (FB) (RNP 1.00)	024.87 / 2.67	3100												
NUNOE	TURVE (TF) (FB) (RNP 1.00)	042.29 / 2.33	3000												
(SEE FORM 8260-10)															
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. PROFILE STARTS AT RIFTS 3. FAC: 050.96 FAF: TURVE DIST FAF TO MAP: 6.32 THLD: _____ 4. MIN. ALT: RIFTS 3400, SLAGS 3400, NUNOE 3100, TURVE 3000, UYZAY 1980 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: _____ TCH: _____ 8. MSA FROM: QITEJ 5600				MAG VAR: 16W EPOCH YEAR: 1995											
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A @											
CATEGORY =====>	A		B		C		D		E						
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
CIRCLING	1720	1 1/4	987	1780	1 1/2	1047	1980	3	1247		NA				
NOTES: CHART NOTE: CIRCLING NA FOR CAT C E OF RWY 1-19. CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON MPV VOR/DME AIRWAY RADIALS 317 CW 037. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BURLINGTON ALTIMETER SETTING AND INCREASE ALL MDAS 120 FEET.															
CITY AND STATE		ELEVATION: 733 TDZE:		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:					
MORRISVILLE, VT		AIRPORT NAME:		MORRISVILLE-STOWE STATE		RNAV (GPS)-A, ORIG 17 AUGUST 2017				AMDT: NONE					
										DATED					



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

<u>FROM</u>	<u>TO</u>	<u>COURSE AND DISTANCE</u>	<u>ALTITUDE</u>
TURVE (FAF)	UYZAY (TF) (FB) (RNP 0.30)	050.96 / 2.90	
UYZAY	QITEJ (MAP) (TF) (FO) (RNP 0.30)	050.96 / 3.42	
QITEJ (MAP)	1133 MSL (CA)	50.96	
1133 MSL	LIQED (DF) (FO) (RNP 1.00)		5600

QUALITY
19
CHECKED

CITY AND STATE
MORRISVILLE, VT

ELEVATION: 733 **TDZE:**
 AIRPORT NAME:
 MORRISVILLE-STOWE STATE

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS)-A, ORIG
 17 AUGUST 2017

SUP:
 AMDT: **NONE**
 DATED: