

<b>RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33</b>				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
<b>TERMINAL ROUTES</b>				<b>MISSED APPROACH</b>											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LP: RW17 LNAV: RW17  CLIMB TO 12000 DIRECT TAYTE AND ON TRACK 173.08 TO JULIK AND HOLD, CONTINUE CLIMB-IN-HOLD TO 12000.  ADDITIONAL FLIGHT DATA: HOLD N, RT, 172.00 INBOUND. CHART FAS OBST: 4829 TREE 392424N/1122954W CHART FAS OBST: 4839 TREE 392503N/1122933W WAAS CHANNEL # 45724 REFERENCE PATH ID: W17A LUSSI TO RW17: 3.00/40. LTP HAE: 1431.5'M											
DTA VORTAC	WUNDI (FO)	346.63 / 21.25	9700												
LOLIC (IAF)	WUNDI (NOPT) (FB)	188.28 / 3.99	9700												
PUCIT (IAF)	WUNDI (NOPT) (FB)	246.97 / 10.05	9700												
WUNDI (IF/IAF)	LUSSI (FB)	166.27 / 10.27	6600												
LUSSI (FAF)	ZOBMA/1.40 NM TO RW17 (FB)	166.27 / 4.25													
ZOBMA/1.40 NM TO RW17	RW17 (MAP) (FO)	166.27 / 1.40													
(SEE FORM 8260-10)															
1. PT <u>      </u> SIDE OF COURSE <u>      </u> OUTBOUND <u>      </u> FT WITHIN <u>      </u> MILES OF <u>      </u> (IAF)															
2. HOLD N WUNDI, LT, 186.27 INBOUND, 9700 FT. IN LIEU OF PT (IAF)															
3. FAC: <u>166.27</u> FAF: <u>LUSSI</u> DIST FAF TO MAP: <u>5.65</u> THLD: <u>5.65</u>															
4. MIN. ALT: <u>WUNDI 9700, LUSSI 6600, ZOBMA/1.40 NM TO RW17 5240</u>															
5. DIST TO THLD FROM OM: <u>      </u> MM: <u>      </u> IM: <u>      </u> 150 HAT: <u>      </u> 100 HAT: <u>      </u> GS ANT: <u>      </u>															
6. MIN GS INCPT: <u>      </u> GS ALT AT: <u>      </u> OM: <u>      </u> MM: <u>      </u> IM: <u>      </u>															
7. GS ANGLE: <u>      </u> TCH: <u>34:1 IS CLEAR</u>															
8. MSA FROM: <u>RW17 11400</u>															
MAG VAR: 14E EPOCH YEAR: 2000															
<b>MINIMUMS</b>															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A X							
CATEGORY ==>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LP MDA	5080	1	321	5080	1	321	5080	1	321	5080	1	321			
LNAV MDA	5100	1	341	5100	1	341	5100	1	341	5100	1	341			
CIRCLING	5140	1	381	5220	1	461	5220	1 1/2	461	5320	2	561			
NOTES: CHART NOTE: CIRCLING TO RWY 30 NA AT NIGHT. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, PROCEDURE NA. CHART NOTE: DME/DME RNP-0.3 NA. CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.															
CITY AND STATE		ELEVATION: 4759 THRE: 4759		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:						SUP:			
DELTA, UT		AIRPORT NAME:		DELTA MUNI		RNAV (GPS) RWY 17, AMDT 1A						AMDT: 1			
						19 SEPTEMBER 2013						DATED 08/25/2011			

QUALITY  
9  
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
**RNAV - STANDARD**  
**INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**TERMINAL ROUTES, (CONT.):**

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW17 (MAP)	5080 MSL	166.27	
5080 MSL	TAVTE (FB)		
TAVTE	JULIK (FO)	173.08 / 8.71	12000

QUALITY  
CHECKED

CITY AND STATE  
 DELTA, UT

ELEVATION: 4759 THRE: 4759  
 AIRPORT NAME:  
 DELTA MUNI

FACILITY  
 IDENTIFIER:  
 RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
 RNAV (GPS) RWY 17, AMDT 1A  
 19 SEPTEMBER 2013

SUP:  
 AMDT: 1  
 DATED: 08/25/2011

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KDTA
RUNWAY	RW17
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W17A
LTP/FTP LATITUDE	392328.1350N
LTP/FTP LONGITUDE	1123007.7820W
LTP/FTP ELLIPSOIDAL HEIGHT	+14315
FPAP LATITUDE	392158.9600N
FPAP LONGITUDE	1123008.3200W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1072
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	0.0

CRC REMAINDER

EC926B92

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K2
LTP ORTHOMETRIC HEIGHT	+14507
FPAP ORTHOMETRIC HEIGHT	+14507

QUALITY  
9  
CHECKED

CITY AND STATE DELTA, UT	ELEVATION: 4759      THRE: 4759 AIRPORT NAME: DELTA MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 17, AMDT 1A 19 SEPTEMBER 2013	SUP: AMDT: 1 DATED: 08/25/2011
-----------------------------	--	---------------------------------	---	--------------------------------------

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet/RVR.

[illegible][illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	KDTAK2FR17	ADTA	010DTA	K2D	0V	IF				18000		A	JS
SUSAP	KDTAK2FR17	ADTA	020WUNDIK2EA0EY	020TF			34660213	+	09700			A	JS
SUSAP	KDTAK2FR17	ADTA	030WUNDIK2EA0EE	AL	HF		18630070	+	09700			A	JS
SUSAP	KDTAK2FR17	ALOLIC	010LLOLICK2EA0E	A	IF					18000		A	JS
SUSAP	KDTAK2FR17	ALOLIC	020WUNDIK2EA0EE	B	010TF		18830040	+	09700			A	JS
SUSAP	KDTAK2FR17	APUCIT	010PUCITK2EA0E	A	IF					18000		A	JS
SUSAP	KDTAK2FR17	APUCIT	020WUNDIK2EA0EE	B	010TF		24700101	+	09700			A	JS
SUSAP	KDTAK2FR17	R	010WUNDIK2EA0E	I	IF			+	09700	18000		A	JS
SUSAP	KDTAK2FR17	R	020LUSSIK2EA1E	F	051TF		16630103	+	06600		RW17	K2PGA	JS
SUSAP	KDTAK2FR17	R	020LUSSIK2EA2WALP			N	ALNAV						JS
SUSAP	KDTAK2FR17	R	021ZOBMAK2EA0E	S	031TF		16630043	V	0524005245	-300		A	JS
SUSAP	KDTAK2FR17	R	030RW17	K2PGOGY	M	031TF	16630014		04799	-300		A	JS
SUSAP	KDTAK2FR17	R	040	O	M	CA	1663	+	05080			A	JS
SUSAP	KDTAK2FR17	R	050TAVTEK2EA0E		DF							A	JS
SUSAP	KDTAK2FR17	R	060JULIKK2EA0EY	010TF			1731	+	12000			A	JS
SUSAP	KDTAK2FR17	R	070JULIKK2EA0EE	R	HM		17200070	+	12000			A	JS

[illegible]

6789012  
BALTIMORE  
CHECKED

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

QUALITY  
9  
SERVED

CITY AND STATE  DELTA, UT	ELEVATION: 4759	THRE: 4759	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME:			RNAV (GPS)-RWY 17, AMDT 1A	AMDT: 1
	DELTA MUNI		RNAV	19 SEPTEMBER 2013	DATED: 08/25/2011

**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE**  
**FLIGHT STANDARDS SERVICES - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH; and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**ARINC SUMMARY - 424-18 - RNAV (GPS)**

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	DTA	DTA	010		IF		FB					
	DTA	WUNDI	020		TF		FO	2.0	346.6 (000.6T)	021.3	AA 09700	
	DTA	WUNDI	030	IAF	HF	L	FO		186.3 (200.3T)	007.0	AA 09700	
	LOLIC	LOLIC	010	IAF	IF		FB					
	LOLIC	WUNDI	020		TF		FB	1.0	188.3 (202.3T)	004.0	AA 09700	
	PUCIT	PUCIT	010	IAF	IF		FB					
	PUCIT	WUNDI	020		TF		FB	1.0	247.0 (261.0T)	010.1	AA 09700	
		WUNDI	010	FACF	IF		FB				AA 09700	
		LUSSI	020	FAP	TF		FB	0.5	166.3 (180.3T)	010.3	AA 06600	
		ZOBMA	021	SDF	TF		FB	0.3	166.3 (180.3T)	004.3	AA 05240	GS 05245
		RW17	030	MAP	TF		FO	0.3	166.3 (180.3T)	001.4	AT 04799	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		166.3 (180.3T)		AA 05080	
	TAVTE	050		DF		FB					
	JULIK	060		TF		FO	1.0	173.1 (187.1T)		AA 12000	
	JULIK	070		HM	R	FO		172.0 (186.0T)	007.0	AA 12000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	DTA	N391807.96	W1123020.00	N3918.133	W11230.333
	JULIK	N390910.82	W1123132.56	N3909.180	W11231.543
	LOLIC	N394305.95	W1122804.40	N3943.099	W11228.073
	LUSSI	N392907.61	W1123005.72	N3929.127	W11230.095
	PUCIT	N394059.53	W1121710.98	N3940.992	W11217.183
	TAVTE	N391749.65	W1123009.83	N3917.828	W11230.164
	WUNDI	N393924.14	W1123001.95	N3939.402	W11230.033
	ZOBMA	N392452.21	W1123007.27	N3924.870	W11230.121
	RW17	N392328.14	W1123007.78	N3923.469	W11230.130

RUNWAY DATA	THRESHOLD	ELEVATION	TCH
RWY			
RW17	04759		40

QUALITY  
9  
CHECKED

CITY AND STATE <b>DELTA, UT</b>	ELEVATION: <b>4759</b>	THRE: <b>4759</b>	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME:			<b>RNAV (GPS) RWY 17, AMDT 1A</b>	AMDT: <b>1</b>
	<b>DELTA MUNI</b>	<b>RNAV</b>		<b>19 SEPTEMBER 2013</b>	DATED: <b>08/25/2011</b>