

**Federal Aviation
Administration**

Transmittal Letter 13-24

OCTOBER 11, 2013

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DAT	SUBJECT
11/14/13	FL	St Augustine	Northeast Florida Rgnl	3/5330	10/10/13	RNAV (GPS) RWY 13, ORIG-A

AIRAC Date: 14 NOVEMBER 2013

FDC 3/5330 SGJ FI/P IAP NORTHEAST FLORIDA RGNL, ST AUGUSTINE, FL. RNAV (GPS) RWY 13, ORIG-A... LNAV MDA 460/HAT 450 ALL CATS. CIRCLING CAT A MDA 480/HAA 470, CAT B/C MDA 580/HAA 570. CHART NOTE: RWY 13 STRAIGHT-IN MINIMUMS NA AT NIGHT. DELETE NOTE: WHEN VGSI INOP, CIRCLING RWY 31 NA AT NIGHT. CHANGE VISIBILITY REDUCTION BY HELICOPTERS NA NOTE TO READ: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. CHANGE LOCAL ALTIMETER SETTING NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE JACKSONVILLE NAS (TOWERS FLD) ALTIMETER SETTING AND INCREASE ALL DA 57 FEET AND ALL MDA 60 FEET; INCREASE LPV AND LNAV/VNAV ALL CATS AND LNAV CAT C AND CIRCLING CAT C VISIBILITY 1/4 MILE. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 54C (130F). THIS IS RNAV (GPS) RWY 13, ORIG-B.