

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: DEKYA
CIRCA (IAF)	PIYIL (NOPT) (FB)	306.93 / 5.00	3400	CLIMBING RIGHT TURN TO 3400 DIRECT PIYIL AND HOLD.
GOMRE (IAF)	PIYIL (NOPT) (FB)	126.71 / 5.00	3400	
PIYIL (IF/IAF)	BOPPA (FB)	036.82 / 10.00	1900	
				ADDITIONAL FLIGHT DATA: CHART FAS OBST: 100 BEACON TWR 663607N/1600009W CHART VDP AT 0.69 MILES TO DEKYA. BOPPA TO RW04: 3.05/45

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD SW PIYIL, RT, 036.82 INBOUND, 3400 FT. IN LIEU OF PT (IAF)
- FAC: 037.13 FAF: BOPPA DIST FAF TO MAP: 5.18 THLD: 5.68
- MIN. ALT: PIYIL 3400, BOPPA 1900
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: GS ALT AT: OM: MM: IM:
- GS ANGLE: TCH: 34:1 IS NOT CLEAR
- MSA FROM:

MAG VAR: 16E

EPOCH YEAR: 2010

MINIMUMS

TAKEOFF:		STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A		STANDARD @									
CATEGORY =====>		A			B			C			D			E		
		DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA		420	1	403	420	1	403	420	1 1/4	403	420	1 1/4	403			
CIRCLING		440	1	423	480	1	463	480	1 1/2	463	580	2	563			

NOTES:

CHART NOTE: CIRCLING TO RWY 9-27 NA AT NIGHT.

CHART NOTE: DME/DME RNP-0.3 NA.

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.

CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.

SEE 8260-10

CITY AND STATE

SELAWIK, AK

ELEVATION: 17 TDZE: 17

AIRPORT NAME:

SELAWIK

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO.:

RNAV (GPS) RWY 4, ORIG
07/05/2007

SUP:

AMDT: NONE

DATED



RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

CHART NOTE: IF LOCAL ALTIMETER SETTING NOT RECEIVED, USE KOTZEBUE ALTIMETER SETTING AND INCREASE ALL MDAS 160 FEET.

CHART NOTE: VDP NA WHEN USING KOTZEBUE ALTIMETER SETTING.

TAA

	FROM	TO	ALT
1.	307/30 CW 023/30 (NOPT)	307/12 CW 023/12	5300
2.	307/12 CW 023/12	PIYIL (IF/IAF) (FB)	3400
	023/30 CW 127/30 (NOPT)	PIYIL (IF/IAF) (FB)	3400
3.	127/30 CW 217/30	GOMRE (IAF) (FB)	4300
4.	217/30 CW 307/30	CIRCA (IAF) (FB)	5000

CITY AND STATE

SELAWIK, AK

ELEVATION: 17 TDZE: 17

AIRPORT NAME:

SELAWIK

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO.:

RNAV (GPS) RWY 4, ORIG

7/5/07

SUP:

AMDT: NONE

DATED:



Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

CITY AND STATE SELAWIK, AK	ELEVATION: 17 TDZE: 17 AIRPORT NAME: SELAWIK	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO.: RNAV (GPS) RWY 4, ORIG 07/05/2007	SUP:
				AMDT: NONE
				DATED:



U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-15

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE
	CIRCA	CIRCA	010	IAF	IF		FB				
	CIRCA	PIYIL	020		TF		FB	1.0	306.9(323T)	005.0	03400
	GOMRE	GOMRE	010	IAF	IF		FB				
	GOMRE	PIYIL	020		TF		FB	1.0	126.7(143T)	005.0	03400
	PIYIL	PIYIL	010		HF	R	FB		036.8(053T)	005.0	03400
		PIYIL	010	FACF	IF		FB				03400
		BOPPA	020	FAF	TF		FB	0.5	036.8(053T)	010.0	01900
		DEKYA	030	MAP	TF		FO	0.3	037.1(053T)	005.2	00201

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE
		040		CA		FB	1.0	037.1(053T)		00417
	PIYIL	050		DF	R	FO	1.0			03400
	PIYIL	060		HM	R	FO	2.0	036.8(053T)	005.0	03400

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	BOPPA	N663226.85	W1601055.41	N6632.448	W16010.924
	CIRCA	N662228.53	W1602320.20	N6622.476	W16023.337
	DEKYA	N663532.41	W1600032.24	N6635.540	W16000.537
	GOMRE	N663024.89	W1603823.20	N6630.415	W16038.387
	PIYIL	N662626.89	W1603050.51	N6626.448	W16030.842
	RW04	N663550.28	W1595931.97	N6635.838	W15959.533

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW04	00017	45

CITY AND STATE SELAWIK, AK	ELEVATION: 17 TDZE: 17	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO.: RNAV (GPS) RWY 4, ORIG 07/05/2007	SUP:
	AIRPORT NAME: SELAWIK			AMDT: NONE
				DATED:

