

U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
 Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
YOSEMITE	ONE	YOSE1.CZQ	NONE		26 MAY 2016

TYPE: SID

DP ROUTE DESCRIPTION:

TAKEOFF RWY 11L/R: CLIMB HEADING 111.35 TO 2000, THENCE...
 TAKEOFF RWY 29L/R: CLIMB HEADING 291.36 TO 2000, THENCE...

...EXPECT RADAR VECTORS TO JOIN ASSIGNED ROUTE. MAINTAIN ASSIGNED ALTITUDE; EXPECT CLEARANCE TO FILED ALTITUDE FIVE MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

Transition Name	Transition Computer Codes	From FIX/NAVAID	To FIX/NAVAID	Course	Distance	MEA	MOCA	Crossing Altitudes/Fixes
-----------------	---------------------------	--------------------	---------------	--------	----------	-----	------	--------------------------

PROCEDURAL DATA NOTES/TAKEOFF MINIMUMS:

NOTE: RADAR REQUIRED.

TAKEOFF MINIMUMS:
 RWY 11L/R: STANDARD.
 RWY 29L/R: STANDARD.

TAKEOFF OBSTACLES NOTES:

NOTE: RWY 11L, SIGN 1693 FEET FROM DER, 863 FEET RIGHT OF CENTERLINE, 51 FEET AGL, 383 FEET MSL. TREE 1420 FEET FROM DER, 667 FEET RIGHT OF CENTERLINE, 375 FEET MSL. TERRAIN 128 FEET FROM DER, 506 FEET RIGHT OF CENTERLINE, 338 FEET MSL. POLE 1228 FEET FROM DER, 664 FEET RIGHT OF CENTERLINE, 33 FEET AGL/365 FEET MSL. TERRAIN 175 FEET FROM DER, 271 FEET LEFT OF CENTERLINE, 338 FEET MSL. POLE 648 FEET FROM DER, 542 FEET LEFT OF CENTERLINE, 16 FEET AGL/349 FEET MSL. ELECTRICAL SYSTEM 1223 FEET FROM DER, 662 FEET RIGHT OF CENTERLINE, 30 FEET AGL/363 FEET MSL.

NOTE: RWY 11R, POLES BEGINNING 1205 FEET FROM DER, 394 FEET RIGHT OF CENTERLINE, UP TO 54 FEET AGL/384 FEET MSL. ELECTRICAL SYSTEM 1598 FEET FROM DER, 294 FEET RIGHT OF CENTERLINE, 57 FEET AGL/386 FEET MSL. TOWER 664 FEET FROM DER, 274 FEET LEFT OF CENTERLINE, 34 FEET AGL/362 FEET MSL. POLES BEGINNING 1598 FEET FROM DER, 263 FEET RIGHT OF CENTERLINE, UP TO 55 FEET AGL/385 FEET MSL. POLE 329 FEET FROM DER, 279 FEET LEFT OF CENTERLINE, 21 FEET AGL/349 FEET MSL.

NOTE: RWY 29L, TREES BEGINNING 998 FEET FROM DER, 14 FEET LEFT OF CENTERLINE, UP TO 396 FEET MSL. TREES BEGINNING 1659 FEET FROM DER, 81 FEET RIGHT OF CENTERLINE, UP TO 379 FEET MSL. POLE 1638 FEET FROM DER, 427 FEET RIGHT OF CENTERLINE, 42 FEET AGL/375 FEET MSL. POLE 998 FEET FROM DER, 620 FEET LEFT OF CENTERLINE, 47 FEET AGL/377 FEET MSL.

NOTE: RWY 29R, POLES BEGINNING 993 FEET FROM DER, 547 FEET RIGHT OF CENTERLINE, UP TO 32 FEET AGL/365 FEET MSL. TREE 2315 FEET FROM DER, 874 FEET LEFT OF CENTERLINE, 395 FEET MSL.

CONTROLLING OBSTACLES:

QUALITY
3
CHECKED

U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
YOSEMITE	ONE	YOSE1.CZQ	NONE		26 MAY 2016

LOST COMMUNICATIONS PROCEDURES:

IF NOT IN CONTACT WITH FRESNO DEPARTURE CONTROL WITHIN TWO MINUTES OF TAKEOFF, AIRCRAFT ENROUTE TO FRA, MVA, FMG AND OAL PROCEED DIRECT FRA VORTAC, CROSS FRA VORTAC AT OR ABOVE 9000 FT, THENCE VIA ASSIGNED ROUTE TO FILED ALTITUDE.

ADDITIONAL FLIGHT DATA:

AIRPORTS SERVED:

FRESNO YOSEMITE INTL

FRESNO, CA

COMMUNICATIONS:

ATIS, CLNC DEL, GND CON, FRESNO DEP CON 119.6, FRESNO TWR.

FIXES AND/OR NAVAIDS:

HYP VOR/DME, FMG VORTAC, MVA VORTAC, OAL VORTAC, FRA VORTAC, CZQ VORTAC, PXN VORTAC.



U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
YOSEMITE	ONE	YOSE1.CZQ	NONE		26 MAY 2016

REMARKS:

COORDINATED WITH:

Mar 29, 2016

ATA, APA, AOPA, NBAA, ALPA, ZOA, FRESNO ATCT, FRESNO APP CON, ARPT MGR, WST FPO.

CHANGES:

1. ORIGINAL.

REASONS:

1. PER ATC REQUEST.



DEPARTURE (DATA RECORD)

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
YOSEMITE	ONE	YOSE1 .CZQ	NONE		26 MAY 2016

ARINC SUMMARY - KFAT

ROUTES

TRANSITION	WPT SEQ	WPT NAME	LEG TYPE	FB/FO	RNP	MAG CRS	REC NAV	ANGLE	TURN DIR	CENTER FIX	TURN RADIUS	ALTITUDE DESCRIPTION & VALUE	SPEED LIMIT DESCRIPTION & VALUE	WPT DESCRIPTION CODE
RW11B	010		VA	FB		111.4						AA 02000		
RW11B	020		VM	FB		111.4								E
RW29B	010		VA	FB		291.4						AA 02000		
RW29B	020		VM	FB		291.4								E

RUNWAYS

RUNWAY	THRESHOLD LATITUDE	THRESHOLD LONGITUDE	THRESHOLD ELEVATION
RW11L	N364702.41	W1194348.31	00333
RW11R	N364659.02	W1194356.71	00330
RW29L	N364613.21	W1194236.44	00330
RW29R	N364609.61	W1194215.82	00332

