

U.S. Department  
of Transportation

800 Independence Ave., S.W.  
Washington, D.C. 20591

**Federal Aviation  
Administration**

**Transmittal Letter 15-26**

**November 26, 2015**

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53  
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure  
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME,  
LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,  
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:  
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
10-Dec-15	WI	Mosinee	Central Wisconsin	5/9662	10/23/15	RNAV (GPS) RWY 26, Amdt 1A

**EFFECTIVE 10 DECEMBER 2015**

FDC **5/9662** CWA IAP CENTRAL WISCONSIN, MOSINEE, WI. RNAV (GPS) RWY 26, AMDT 1A... LPV DA 1510, VIS 3/4 ALL CATS. LNAV/VNAV DA 1730 ALL CATS. LNAV HAT 420 ALL CATS. DELETE NOTE: WHEN VGSI INOP, STRAIGHT-IN/CIRCLING RWY 26 NA AT NIGHT. DELETE NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHANGE LOCAL ALTIMETER SETTING NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE WAUSAU ALTIMETER SETTING AND INCREASE ALL DA 32 FEET AND ALL MDA 40 FEET; AND INCREASE LPV AND LNAV/VNAV ALL CATS VISIBILITY 1/8 MILE AND LNAV CAT C/D 1/4 MILE. CHART NOTE: VDP NA WHEN USING WAUSAU ALTIMETER SETTING. CHART VDP AT 1.17 MILES TO RW26\*. 34:1 IS CLEAR. TDZE 1260. THIS IS RNAV (GPS) RWY 26, AMDT 1B. 1510202141-PERM