

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW26 (MAP)	1510 MSL	257.42	
1510 MSL	PLEAD (FO)		3000

NOTES, (CONT.):

*RNAV ONLY

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE WAUSAU ALTIMETER SETTING AND INCREASE ALL DA 32 FEET AND ALL MDA 40 FEET, AND INCREASE RNAV/VNAV ALL CATS VISIBILITY 1/8 MILE AND INCREASE RNAV CATS C AND D VISIBILITY 1/4 MILE.

CHART NOTE: WHEN VGS1 INOP, STRAIGHT-IN/CIRCLING RWY 26 NA AT NIGHT.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT USERS ON V191 NORTHWEST BOUND.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT IPUCO ON V55 EASTBOUND.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON STE VORTAC AIRWAY RADIALS 354 CW 090.

CITY AND STATE
MOSINEE, WI

ELEVATION: 1277 THRE: 1260
AIRPORT NAME:
CENTRAL WISCONSIN

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 26, AMDT 1
05 MAY 2011

SUP:
AMDT: ORIG
DATED: 05/17/2001

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0
SBAS SERVICE PROVIDER IDENTIFIER 0
AIRPORT IDENTIFIER KCWA
RUNWAY RW26
APPROACH PERFORMANCE DESIGNATOR 0
ROUTE INDICATOR 0
REFERENCE PATH DATA SELECTOR 0
REFERENCE PATH IDENTIFIER (APPROACH ID) W26A
LTP/FTP LATITUDE 444704.0795N
LTP/FTP LONGITUDE 0893848.4720W
LTP/FTP ELLIPSOIDAL HEIGHT +03488
FPAP LATITUDE 444644.6100N
FPAP LONGITUDE 0894050.5400W
THRESHOLD CROSSING HEIGHT (TCH) 00045.0
TCH UNITS SELECTOR (METERS OR FEET USED) F
GLIDEPATH ANGLE (GPA) 03.00
COURSE WIDTH AT THRESHOLD 106.75
LENGTH OFFSET 0416
HORIZONTAL ALERT LIMIT (HAL) 40.0
VERTICAL ALERT LIMIT (VAL) 50.0

CRC REMAINDER

07EDB47D

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K5
LTP ORTHOMETRIC HEIGHT +03840
FPAP ORTHOMETRIC HEIGHT +03840

CITY AND STATE

MOSINEE, WI

ELEVATION: 1277

THRE: 1260

AIRPORT NAME:

CENTRAL WISCONSIN

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 26, AMDT 1

05 MAY 2011

SUP:

AMDT: ORIG

DATED: 05/17/2001

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
A
CYCLES

CITY AND STATE MOSINEE, WI	ELEVATION: 1277 THRE: 1260 AIRPORT NAME: CENTRAL WISCONSIN	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:	SUP:
			RNAV (GPS) RWY 26, AMDT 1	AMDT: ORIG
			05 MAY 2011	DATED: 05/17/2001

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

SUSAP KCWAK5GRW26 0076482574 N44470408W089384847+0200 +0348801260000045150R

SUSAP KCWAK5PR26 RW26 001 0000W26A0N4447040795W08938484720+034880300N4446446100W08940505400106750416000450F40050007EDB47D
SUSAP KCWAK5PR26 RW26 002E +03840+03840LFP 58220

SUSAP KCWAK5SRW26 K5PG	0	18018003625	M
------------------------	---	-------------	---

3/11/74
A
CHECKED

SUP:	
AMDT:	ORIG
DATED:	05/17/2001