

<b>U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION</b> <b>NDB STANDARD INSTRUMENT APPROACH PROCEDURE</b> <b>FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27</b>								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
<b>TERMINAL ROUTES</b>										<b>MISSED APPROACH</b>									
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: RYB NDB									
MHZ VORTAC		RYB NDB		243.31 / 17.70				3500		CLIMBING LEFT TURN TO 3500 ON HEADING 274 AND ON RYB NDB BRG-313 THEN DIRECT RYB NDB AND HOLD.									
HEDUD INT		RYB NDB		124.10 / 17.30				3500											
														<b>ADDITIONAL FLIGHT DATA:</b> HOLD NW, RT, 133.23 INBOUND. FAS OBST: 559 AAO 322315N/0903211W CHART 3500 PRIOR TO RYB NDB IN PROFILE. CHART 3500 PRIOR TO RYB NDB IN PROFILE. CHART CIRCLING ICON. FAC CROSSES RWY CIL EXTENDED 3002 FROM THLD.					
1. PT <u>L</u> SIDE OF COURSE <u>313.23</u> OUTBOUND <u>2100</u> FT WITHIN <u>10</u> MILES OF <u>RYB NDB</u> (IAF)														MAG VAR: 0E      EPOCH YEAR: 2010					
2.																			
3. FAC <u>133.23</u> FAF _____ DIST FAF TO MAP _____ THLD _____																			
4. MIN. ALT _____																			
8. MSA FROM: RYB NDB 3500																			
<b>MINIMUMS</b>																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT      ALTERNATE: N A      STANDARD @																			
CATEGORY >>>>>	A			B			C			D			E						
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA				
S-12	920	1	680	920	1	680	920	1 7/8	680	920	1 7/8	680							
CIRCLING	920	1	673	920	1	673	980	2	733	980	2 1/4	733							
<b>NOTES:</b> CHART NOTE: CIRCLING TO RWY 30 NA AT NIGHT. CHART NOTE: CIRCLING NA FOR CAT D SOUTHWEST OF RWYS 12 AND 30. CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. (SEE FORM 8260-10)																			
CITY AND STATE				ELEVATION: 247      THRE: 240				FACILITY IDENTIFIER:				PROCEDURE NO/AMDT NO/EFFECTIVE DATE:				SUP			
RAYMOND, MS				AIRPORT NAME:				RYB				NDB RWY 12, AMDT 3, 8/22/2013				AMDT 2			
				JOHN BELL WILLIAMS												DATE 08/25/2011			

TU315 Pub 8/22/13

NDB STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.27

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

## NOTES, (CONT.):

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HAWKINS FIELD ALTIMETER SETTING:

INCREASE ALL MDA 40 FT, S-12 CAT C AND D VISIBILITIES 1/8 MILE, AND CIRCLING CAT C AND D VISIBILITIES 1/4 MILE.

CITY AND STATE

RAYMOND, MS

ELEVATION: 247

THRE: 240

AIRPORT NAME:

JOHN BELL WILLIAMS

FACILITY  
IDENTIFIER:  
RYB

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:

NDB RWY 12, AMDT 3, 8/22/2013

SUP:

AMDT: 2

DATED: 08/25/2011