

**Federal Aviation
Administration**

Transmittal Letter 15-21

August 28, 2015

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
15-Oct-15	KY	Louisville	Louisville Intl- Standiford Field	5/6021	08/24/15	ILS OR LOC RWY 35R , ILS RWY 35R (SA CAT I), ILS RWY 35R (CAT II & III), Amdt 4C

AIRAC Date: 15 October 2015

FDC **5/6021** SDF IAP LOUISVILLE INTL-STANDIFORD FIELD, LOUISVILLE, KY. ILS OR LOC RWY 35R, AMDT 4C ... ILS RWY 35R (SA CAT I), AMDT 4C ... ILS RWY 35R (CAT II AND III), AMDT 4C ... HOSTO INT/I-JJM 4.1 DME/RADAR MINIMUM ALTITUDE *1380. S-LOC 35R MDA 1380/HAT 900 ALL CATS, VISIBILITY CAT A-B RVR 4000. CIRCLING CAT A-C MDA 1380/HAA 879, CAT D MDA 1400/HAA 899, VISIBILITY CAT D 3. HOSTO FIX MINIMUMS (DUAL VOR RECEIVERS OR DME OR RADAR REQUIRED): S-LOC 35R VISIBILITY CAT C-D RVR 2600, CIRCLING CAT C MDA 1160/HAA 659, CAT D MDA 1400/HAA 899, VISIBILITY CAT D 3. CHART CIRCLING ICON. ALTERNATE MINIMUMS: CAT A/B 900-2, CAT C 900-2 1/2, CAT D 900-3. THIS IS ILS OR LOC RWY 35R, AMDT 4D...ILS RWY 35R (SA CAT I), AMDT 4D...ILS RWY 35R (CAT II AND III), AMDT 4D... 1508201155-PERM