

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE	MAP: BWG 18.94 DME FIX
BWG VORTAC (IAF)	ZONBO/BWG 7.00 DME	244.54 / 7.00	2400	CLIMBING RIGHT TURN TO 2400 ON BWG VORTAC R-245 TO CARDE/BWG 14.00 DME AND HOLD.
ZONBO/BWG 7.00 DME (IF)	CARDE/BWG 14.00 DME	244.54 / 7.00 (BWG R-245)	2400	
				ADDITIONAL FLIGHT DATA: HOLD NE, RT, 244.54 INBOUND. CHART FAS OBST: 959 TREE 364912N/0864833W CARDE TO RW24: 3.25/43 CHART BOWLING GREEN ASOS

1. PT        SIDE OF COURSE        OUTBOUND        FT WITHIN        MILES OF        (IAF)  
2. PROFILE STARTS AT ZONBO/BWG 7.00 DME  
3. FAC 244.54 FAF CARDE/BWG 14.00 DME DIST FAF TO MAP        THLD 4.94  
4. MIN. ALT ZONBO 2400, CARDE 2400, YARUC/BWG 16.74 DME 1380  
8. MSA FROM: BWG VORTAC 090-360 3100, 360-090 2700

MAG VAR: 2E

EPOCH YEAR: 1965

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		X						
CATEGORY >>>>>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-24	1280	1	625	1280	1	625		NA			NA				
CIRCLING	1340	1	651	1340	1	651		NA			NA				

NOTES:

CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.  
CHART NOTE: USE BOWLING GREEN ALTIMETER SETTING; WHEN NOT RECEIVED, USE CLARKSVILLE ALTIMETER SETTING AND INCREASE ALL MDA 40 FEET.

(SEE FORM 8260-10)

CITY AND STATE RUSSELLVILLE, KY	ELEVATION: 689 AIRPORT NAME:  RUSSELLVILLE-LOGAN COUNTY	THRE: 655  FACILITY IDENTIFIER: BWG	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR/DME RWY 24, AMDT 7 19 SEPTEMBER 2013	SUP VOR/DME OR GPS RWY 24
				AMDT 6
				DATE 02/19/2004

QUALITY  
CHECKED

## U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

## NOTES, (CONT.):

CHART NOTE: PROCEDURE NA AT NIGHT.

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON BWG VORTAC AIRWAY RADIALS 192 CW 303.

QUALITY  
CHECKED

CITY AND STATE RUSSELLVILLE, KY	ELEVATION: 689 THRE: 655 AIRPORT NAME: RUSSELLVILLE-LOGAN COUNTY	FACILITY IDENTIFIER: BWG	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR/DME RWY 24, AMDT 7 19 SEPTEMBER 2013	SUP: VOR/DME OR GPS RWY 24 AMDT: 6 DATED: 02/19/2004
------------------------------------	--	--------------------------------	---	---