

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW17R CLIMB TO 1000 THEN CLIMBING RIGHT TURN TO 3500 DIRECT GARDS AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SW, RT, 042.05 INBOUND. CHART FAS OBST: 644 TREE 301302N/0974126W 750 AAO 301608N/0974015W DISTANCE TO THLD FROM 200 HAT: 0.44 NM. CHART VDP AT 0.93 NM TO RW17R* *LNAV ONLY. WAAS CHANNEL # 77530 REFERENCE PATH ID: W17B CHART CIRCLING ICON. LTP HAE: 139 M					
CHADE (IAF)		UTEEE (TF) (FB) (RNP 1.00)		174.69 / 6.25				2500							
HOUKM (IAF)		UTEEE (TF) (FB) (RNP 1.00)		147.56 / 7.68				2500							
JEDYE (IAF)		UTEEE (TF) (FB) (RNP 1.00)		204.74 / 4.54				2500							
UTEEE (IF)		BRAZA (TF) (FB) (RNP 1.00)		174.70 / 1.00				2200							
BRAZA		ELLBJ (TF) (FB) (RNP 1.00)		174.69 / 2.00				1600							
(SEE FORM 8260-10)															
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. PROFILE STARTS AT UTEEE 3. FAC: 174.68 FAF: ELLBJ DIST FAF TO MAP: 3.14 THLD: 3.14 4. MIN. ALT: UTEEE 2500, BRAZA 2200, ELLBJ 1600 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 1600 GS ALT AT: ELLBJ 1600 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 59.3 34:1 IS CLEAR 8. MSA FROM: RW17R 3100										MAG VAR: 4E		EPOCH YEAR: 2020			
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @					
CATEGORY =====>		A		B		C		D		E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	742	4000	200	742	4000	200	742	4000	200	742	4000	200	742	4000	200
LNAV/VNAV DA	834	4000	292	834	4000	292	834	4000	292	834	4000	292	834	4000	292
LNAV MDA	900	4000	358	900	4000	358	900	4000	358	900	4000	358	900	4000	358
CIRCLING	1040	1	498	1100	1	558	1200	1 3/4	658	1200	2	658	1520	3	978
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -6C (22F) OR ABOVE 54C (130F). @ CAT E 1000-3 CHART NOTE: SIMULTANEOUS APPROACH AUTHORIZED. CHART NOTE: LNAV PROCEDURE NA DURING SIMULTANEOUS OPERATIONS. CHART NOTE: USE OF FD OR AP PROVIDING RNAV TRACK GUIDANCE REQUIRED DURING SIMULTANEOUS OPERATIONS. (CONTINUED ON PAGE 2)															
CITY AND STATE		ELEVATION: 542 TDZE: 542		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:					
AUSTIN, TX		AIRPORT NAME:		AUSTIN-BERGSTROM INTL		RNAV (GPS) Y RWY 17R, AMDT 2				AMDT: 1B					
						7 DECEMBER 2017				DATED 08/20/2015					



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
ELLBJ (FAF)	RW17R (MAP) (TF) (FO) (RNP 0.30)	174.68 / 3.14	
RW17R (MAP)	1000 MSL (CA)	174.68	1000
1000 MSL	GARDS (DF) (FO) (RNP 1.00)		3500

NOTES, (CONT.):

CHART NOTE: DME/DME RNP-0.3 NA.

CHART NOTE: FOR INOPERATIVE ALS, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO RVR 4500. INCREASE LNAV VISIBILITY ALL CATS TO RVR 5500.

QUALITY
16
CHECKED

CITY AND STATE

AUSTIN, TX

ELEVATION: 542

TDZE: 542

AIRPORT NAME:

AUSTIN-BERGSTROM INTL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) Y RWY 17R, AMDT 2

7 DECEMBER 2017

SUP:

AMDT: 1B

DATED: 08/20/2015

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KAUS
RUNWAY	RW17R
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	Y
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W17B
LTP/FTP LATITUDE	301249.0180N
LTP/FTP LONGITUDE	0974045.7130W
LTP/FTP ELLIPSOIDAL HEIGHT	+01390
FPAP LATITUDE	301047.7955N
FPAP LONGITUDE	0974042.5085W
THRESHOLD CROSSING HEIGHT (TCH)	00059.3
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0000
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0

CRC REMAINDER

092F03C3

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+01650
FPAP ORTHOMETRIC HEIGHT	+01650

QUALITY
16
CHECKED

CITY AND STATE AUSTIN, TX	ELEVATION: 542 AIRPORT NAME: AUSTIN-BERGSTROM INTL	TDZE: 542 RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) Y RWY 17R, AMDT 2 7 DECEMBER 2017	SUP:
				AMDT: 1B
				DATED: 08/20/2015