

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.												
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LNAV: RW07 CLIMBING LEFT TURN TO 4400 DIRECT BLAYR AND HOLD. ADDITIONAL FLIGHT DATA: FAS OBST: 2339 AAO 402620N/0784800W						
JST VORTAC		BLAYR (FO)		297.45 / 7.27				4400								
REC VOR/DME		BLAYR (FO)		232.53 / 15.81				4400								
BLAYR (IF/IAF)		ALLAC (FB)		065.52 / 6.11				3800								
ALLAC (FAF)		CHIMS/1.90 NM TO RW07 (FB)		065.59 / 3.29												
CHIMS/1.90 NM TO RW07		RW07 (MAP) (FO)		065.59 / 1.90												
RW07 (MAP)		2499 MSL		065.59				4400								
2499 MSL		BLAYR (FO)														
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD SW BLAYR, LT, 065.52 INBOUND, 4400 FT. IN LIEU OF PT (IAF) 3. FAC: <u>065.59</u> FAF: <u>ALLAC</u> DIST FAF TO MAP: <u>5.19</u> THLD: <u>5.19</u> 4. MIN. ALT: BLAYR 4400, ALLAC 3800, CHIMS/1.90 NM TO RW07 2740 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u> </u> TCH: <u>34:1</u> IS NOT CLEAR 8. MSA FROM: RW07 4400																
										MAG VAR: 9W			EPOCH YEAR: 1985			
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A X								
CATEGORY =====>		A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LNAV MDA	2600	1	512	2600	1	512	2600	1 1/2	512		NA					
CIRCLING	2780	1	681	2940	1 1/4	841	2940	2 1/2	841		NA					
JOHNSTOWN ALTIMETER SETTING MINIMUMS																
LNAV MDA	2640	1	552	2640	1	552	2640	1 1/2	552		NA					
CIRCLING	2820	1	721	2980	1 1/4	881	2980	2 3/4	881		NA					
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: OBTAIN LOCAL ALTIMETER SETTING ON CTAF; WHEN NOT RECEIVED, USE JOHNSTOWN ALTIMETER SETTING. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON JST VORTAC AIRWAY RADIALS 236 CW 326. (SEE FORM 8260-10)																
CITY AND STATE		ELEVATION: 2099 TDZE: 2088				FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDТ NO./EFFECTIVE DATE:				SUP: <u>4</u>				
EBENSBURG, PA		AIRPORT NAME: EBENSBURG				RNAV		RNAV (GPS) RWY 7, ORIG-A 7 JANUARY 2016				AMDТ: <u>ORIG</u>				
												DATED 05/07/2009				

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART PROFILE NOTE: DESCENT ANGLE NA.

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.

CITY AND STATE

EBENSBURG, PA

ELEVATION: 2099

TDZE: 2088

AIRPORT NAME:

EBENSBURG

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 7, ORIG-A

7 JANUARY 2016

SUP:

AMDT:

DATED:

QUALITY
4

ORIG
CHECKED

05/07/2009

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 9G8

ROUTES

TRANSITION	WPT SEQ	WPT NAME	LEG TYPE	FB/FO	RNP	MAG CRS	REC NAV	ANGLE	TURN DIR	CENTER FIX	TURN RADIUS	ALTITUDE DESCRIPTION & VALUE	SPEED LIMIT DESCRIPTION & VALUE	WPT DESCRIPTION CODE
JST	010	JST	IF	FB										V
JST	020	BLAYR	TF	FO	2.0	297.5						AA 04400		EY
JST	030	BLAYR	HF	FO		065.5			L			AA 04400		EE A
REC	010	REC	IF	FB										V
REC	020	BLAYR	TF	FO	2.0	232.5						AA 04400		EY
REC	030	BLAYR	HF	FO		065.5			L			AA 04400		EE A
	010	BLAYR	IF	FB								AA 04400		E I
	020	ALLAC	TF	FB	0.5	065.5				RW07		AA 03800		E F
	021	CHIMS	TF	FB	0.3	065.6						AA 02740		E S
	030	RW07	TF	FO	0.3	065.6		0.00				AT 02640		GY M
	040		CA	FB		065.6						AA 02499		M
	050	BLAYR	DF	FO					L			AA 04400		EY
	060	BLAYR	HM	FO		065.5			L			AA 04400		EE

POINTS

POINT NAME	LATITUDE	LONGITUDE
JST	N401900.22	W0785003.00
REC	N403247.25	W0784449.28
ALLAC	N402440.35	W0785223.54
BLAYR	N402117.99	W0785904.16
CHIMS	N402628.91	W0784848.05

RUNWAYS

RUNWAY	THRESHOLD LATITUDE	THRESHOLD LONGITUDE	THRESHOLD ELEVATION	PROCEDURE TCH
RW07	N402731.64	W0784643.33	02080	

CITY AND STATE EBENSBURG, PA	ELEVATION: 2099 TDZE: 2088	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 7, ORIG-A 7 JANUARY 2016	SUP: 4
	AIRPORT NAME: EBENSBURG			AMDT: ORIG
	DATED: 05/07/2009			

QUALITY
4
CHECKED