


<b>US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION</b>				<b>RNAV (RNP) - STANDARD, INSTRUMENT APPROACH PROCEDURE, TITLE 14 CFR PART 97.33</b>				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH									
FROM		TO		COURSE AND DISTANCE				ALTITUDE		<b>RNP: DA</b>  CLIMB TO 7500 ON TRACK 026.01 TO TOCYU LEFT TURN TO UFGOD, THEN TRACK 252.59 TO TERRE AND HOLD.  ADDITIONAL FLIGHT DATA: HOLD N, RT, 179.98 INBOUND. DISTANCE TO THLD FROM 269 HAT: 0.68 NM. ROUTE TYPE: A, H ROUTE TYPE QUALIFIER 1: F ROUTE TYPE QUALIFIER 2: S									
LUDIC		HUDEP (TF) (FB) (RNP 2.00)		218.61 / 17.52				10500											
HUDEP (IAF)		OKVIE (TF) (FB) (RNP 1.00)		218.40 / 4.89				9300											
CHEER (IAF)		VIPUC (TF) (FB) (RNP 1.00)		015.02 / 9.35				7000											
ZELOR (IAF)		ROCCA (TF) (FB) (RNP 1.00)		055.58 / 10.24				7500											
OKVIE (IF)		JEDUX (RF) (FB) (RNP 0.70)		(6.35 NM RADIUS CW (CFDVG))/7.41				8600											
(SEE FORM 8260-10)  THIS IS A CORRECTED COPY OF A PROCEDURE ORIGINALLY PUBLISHED IN TL 18-26.																			
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. <b>PROFILE STARTS AT UGADE</b> 3. FAC: <u>025.96</u> FAF: _____ DIST FAF TO MAP: _____ THLD: _____ 4. MIN. ALT: <b>UGADE 6500</b> 5. DIST TO THLD FROM OM: <u>5.36</u> MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: <u>6500</u> GS ALT AT: <b>UGADE 6500</b> OM: _____ MM: _____ IM: _____ 7. GS ANGLE: <u>3.00</u> TCH: <u>50.0</u> 20:1 IS CLEAR 34:1 IS CLEAR 8. MSA FROM: <b>RW03 9000</b>																MAG VAR: 12E		EPOCH YEAR: 2020	
<b>MINIMUMS</b>																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD									
CATEGORY =====>		A		B		C		D		E									
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA				
<b>AUTHORIZATION REQUIRED</b>																			
RNP 0.11 DA	5013	7/8	269	5013	7/8	269	5013	7/8	269	5013	7/8	269							
RNP 0.30 DA	5071	1	327	5071	1	327	5071	1	327	5071	1	327							
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, PROCEDURE NA BELOW -27C OR ABOVE 49C. CHART SPEED ICON IN PLANVIEW AT OKVIE : MAX 230 KIAS. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT LUDIC ON V330 EAST BOUND. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT CHEER ON V21 SOUTH BOUND. (CONTINUED ON PAGE 2)																			
CITY AND STATE		ELEVATION: 4744 TDZE: 4744		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP: RNAV (RNP) Z RWY 2									
IDAHO FALLS, ID		AIRPORT NAME:		IDAHO FALLS RGNL		RNAV (RNP) Z RWY 3, AMDT 1				AMDT: ORIG-B									
						3 JANUARY 2019				DATED 04/28/2016									



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.	
RNAV (RNP) - STANDARD, INSTRUMENT APPROACH PROCEDURE, - TITLE 14 CFR PART 97.33					
TERMINAL ROUTES, (CONT.):					
FROM		TO	COURSE AND DISTANCE	ALTITUDE	
JEDUX	UGADE (RF) (FB) (RNP 0.70)		(4.94 NM RADIUS CW (CFDVJ))/8.70	6500	
VIPUC (IF)	UGADE (TF) (FB) (RNP 1.00)		025.90 / 6.04	6500	
ROCCA (IF)	FOXUG (TF) (FB) (RNP 1.00)		084.08 / 7.04	7000	
FOXUG	UGADE (RF) (FB) (RNP 1.00)		(6.86 NM RADIUS CCW (CFDVM))/6.99	6500	
UGADE (FAF)	RW03 (MAP) (TF) (FO) (RNP 0.30)		025.96 / 5.36		
RW03 (MAP)	TOCYU (TF) (FB) (RNP 1.00)		026.01 / 7.00		
TOCYU	UFGOD (RF) (FB) (RNP 1.00)		(5.80 NM RADIUS CCW (CFDVL)) / 13.50		
UFGOD	TERRE (TF) (FO) (RNP 1.00)		252.59 / 10.34		
NOTES, (CONT.):					
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT ZELOR ON V365 SOUTHWEST BOUND.					
CHART PLANVIEW NOTE AT LUDIC: (RNP 0.70).					
PBN REQUIREMENTS NOTE: RNP AR APCH.					
PBN REQUIREMENTS NOTE: RF REQUIRED. 					
<div>QUALITY 4 CHECKED</div>					
CITY AND STATE	ELEVATION: 4744	TDZE: 4744	FACILITY IDENTIFIER:	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP: RNAV (RNP) Z RWY 2
IDAHO FALLS, ID	AIRPORT NAME:		RNAV	RNAV (RNP) Z RWY 3, AMDT 1	AMDT: ORIG-B
	IDAHO FALLS RGNL			3 JANUARY 2019	DATED: 04/28/2016