U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
TACAN OR VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

FROM	TO	COURSE AND DISTANCE	ALTITUDE
MHZ VORTAC	ZIKET/12.81 DME	168.83 / 12.81	2100
ENAKE/20.00 DME CW (IAF)	HUXAP/20.00 DME (NOPT)	20.00 DME ARC (MHZ LR-163)	3500
ZIPGI/20.00 DME CCW (IAF)	HUXAP/20.00 DME (NOPT)	20.00 DME ARC (MHZ LR-175)	3500
OBUJI/20.00 DME CW (IAF)	HUXAP/20.00 DME (NOPT)	20.00 DME ARC (MHZ LR-163)	3500
WUDVI/20.00 DME CCW (IAF)	HUXAP/20.00 DME (NOPT)	20.00 DME ARC (MHZ LR-175)	3500
HUXAP/20.00 DME (IF)	ZIKET/12.81 DME	348.83 / 7.19 (MHZ R-169)	2000

MISSED APPROACH

MAP: MHZ 7.84 DME FIX

CLIMBING RIGHT TURN TO 3000 ON HEADING 120 AND MHZ VORTAC R-134 TO RAKIN INT/MHZ 16.54 DME AND HOLD.

ADDITIONAL FLIGHT DATA:

HOLD SE, RT, 314.22 INBOUND.
FAS OBST: 659 AAO 321513N/0900129W
CHART MHZ R-094 AT ENAKE.
CHART MHZ R-274 AT ZIPGI.
CHART MHZ R-233 AT WUDVI.
CHART MHZ R-134 AT OBUJI.
ZIKET TO RW34R: 2.99/66.
CHART CIRCLING ICON

1. PT L SIDE OF COURSE 168.83 OUTBOUND 2100 FT WITHIN 15 MILES OF ZIKET (IAF)
2.
3. FAC 348.83 FAF ZIKET/12.81 DME DIST FAF TO MAP THLD 5.00
4. MIN. ALT ZIKET 2000
8. MSA FROM: MHZ VORTAC 3500

MAG VAR: 1W EPOCH YEAR:2015

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT ALTERNATE: N A STANDARD @

CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-34R	920	5500	574	920	5500	574	920	1 5/8	574	920	1 5/8	574	920	1 5/8	574
CIRCLING	920	1	574	920	1	574	920	1 1/2	574	960	2	614	1040	2 1/2	694

NOTES:

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HAWKINS FIELD ALTIMETER SETTING AND INCREASE ALL MDA 20 FEET; INCREASE S-34R CATS C/D/E VISIBILITY 1/8 MILE.
CHART NOTE: CIRCLING NA FOR CAT E SW OF RWY 16R-34L.
CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.

@ CAT E 800-2 1/2
@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

CITY AND STATE	ELEVATION: 346 THRE: 346	FACILITY IDENTIFIER:	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP
JACKSON, MS	AIRPORT NAME:	MHZ	VOR/DME OR TACAN RWY 34R, ORIG, 08/22/2013	AMDT NONE
	JACKSON-MEDGAR WILEY EVERS INTERNATIONAL			DATE