

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.															
TERMINAL ROUTES										MISSED APPROACH									
FROM		TO			COURSE AND DISTANCE			ALTITUDE		LNAV: RW08 CLIMB TO 600, THEN CLIMBING RIGHT TURN TO 7000 DIRECT NUTUW AND HOLD, CONTINUE CLIMB-IN-HOLD TO 7000. ADDITIONAL FLIGHT DATA: HOLD SW, RT, 027.96 INBOUND. CHART FAS OBST: 329 TREE 594515N/1545612W. 550 AAO 594541N/1550201W 1050 AAO 594640N/1551339W CHART VDP AT 1.10 NM TO RW08. CHART CIRCLING ICON. RUJUV TO RW08: 3.00/35 CHART NAKNEK 2 MOA									
YEGUV (IAF)		BEEKS (NOPT) (TF) (FB) (RNP 1.00)			167.83 / 10.00			5000											
OTUWE (IAF)		BEEKS (NOPT) (TF) (FB) (RNP 1.00)			347.81 / 10.00			5000											
BEEKS (IF/IAF)		JIBUG (TF) (FB) (RNP 1.00)			077.82 / 8.30			3800											
JIBUG		RUJUV (TF) (FB) (RNP 1.00)			078.06 / 2.68			3100											
RUJUV (FAF)		FEBOD/3.68 NM TO RW08 (TF) (FB) (RNP 0.30)			078.13 / 5.34														
(SEE FORM 8260-10)																			
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD W BEEKS, RT, 077.82 INBOUND, 5000 FT. IN LIEU OF PT (IAF) 3. FAC: 078.13 FAF: RUJUV DIST FAF TO MAP: 9.02 THLD: 9.02 4. MIN. ALT: BEEKS 5000, JIBUG 3800, RUJUV 3100, FEBOD/3.68 NM TO RW08 1400 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: _____ TCH: 20:1 IS CLEAR 34:1 IS NOT CLEAR 8. MSA FROM: _____																MAG VAR: 14E		EPOCH YEAR: 2020	
MINIMUMS																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @									
CATEGORY =====>		A			B			C			D			E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA				
LNAV MDA	580	1	388	580	1	388	580	1 1/8	388	580	1 1/8	388							
CIRCLING	740	1	548	740	1	548	800	1 3/4	608	1700	3	1508							
NOTES: CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, PROCEDURE NA. CHART NOTE: RWY 8 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHART NOTE: DME/DME RNP-0.3 NA.																			
CITY AND STATE		ELEVATION: 192 TDZE: 192			FACILITY IDENTIFIER: RNAV			PROCEDURE NO./AMDT NO./EFFECTIVE DATE:			SUP: RNAV (GPS) RWY 7								
ILIAMNA, AK		AIRPORT NAME: ILIAMNA						RNAV (GPS) RWY 8, AMDT 4 13 SEPTEMBER 2018			AMDT: 3								
											DATED 03/12/2009								



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

<u>FROM</u>	<u>TO</u>	<u>COURSE AND DISTANCE</u>	<u>ALTITUDE</u>
FEBOD/3.68 NM TO RW08	RW08 (MAP) (TF) (FO) (RNP 0.30)	078.13 / 3.68	
RW08 (MAP)	600 MSL (CA)	078.13	600
600 MSL	NUTUW (DF) (FO) (RNP 1.00)		7000

TAA

	<u>FROM</u>	<u>TO</u>	<u>ALT</u>
1.	348/30 CW 168/30 (NOPT)	BEEKS (IF/IAF) (FB)	5000
2.	168/30 CW 258/30	YEGUV (IAF) (FB)	6000
3.	258/30 CW 348/30	OTUWE (IAF) (FB)	5200

QUALITY
10
CHECKED

CITY AND STATE ILIAMNA, AK	ELEVATION: 192 AIRPORT NAME: ILIAMNA	TDZE: 192	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 8, AMDT 4 13 SEPTEMBER 2018	SUP: RNAV (GPS) RWY 7
					AMDT: 3
					DATED: 03/12/2009