

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH				
FROM	TO	COURSE AND DISTANCE	ALTITUDE					
MON VOR/DME	HIMOP (FB)	153.04 / 24.98	2500	LNAV: RW01				
HIMOP (IAF)	HEGOG (NOPT) (FB)	101.75 / 7.00	2500					
JUDUN (IAF)	HEGOG (NOPT) (FB)	281.90 / 7.65	2500	CLIMB TO 2000 DIRECT OZIGE AND HOLD.				
HEGOG (IF/IAF)	AKIDY (FB)	011.82 / 6.33	1800					
				ADDITIONAL FLIGHT DATA: HOLD N, RT, 191.89 INBOUND. FAS OBST: 339 AAO 331545N/0912123W AKIDY TO RW01: 3.04/40. CHART GREENVILLE ASOS.				
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD S HEGOG, RT, 011.82 INBOUND, 2500 FT. IN LIEU OF PT (IAF) 3. FAC: 011.84 FAF: AKIDY DIST FAF TO MAP: 5.06 THLD: 5.06 4. MIN. ALT: HEGOG 2500, AKIDY 1800 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: _____ TCH: 34:1 IS CLEAR 8. MSA FROM: RW01 1800								
				MAG VAR: 2E EPOCH YEAR: 2000				
MINIMUMS								
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	X			
CATEGORY =====>	A		B		C		D	
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS
LNAV MDA	680	1	555	680	1	555	680	1 3/4
CIRCLING	680	1	555	680	1	555	720	2
NOTES: CHART NOTE: CIRCLING NA EAST OF RWY 1/19. CHART NOTE: DME/DME RNP-0.3 NA. CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT. CHART NOTE: USE GREENVILLE ALTIMETER SETTING; WHEN NOT RECEIVED, USE MONTICELLO ALTIMETER SETTING SEE 8260-10								
CITY AND STATE		ELEVATION: 125 TDZE: 125		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:		SUP:
LAKE VILLAGE, AR		AIRPORT NAME:		RNAV		RNAV (GPS) RWY 1, ORIG 11 FEB 2010		AMDT: NONE
		LAKE VILLAGE MUNI						DATED

QUALITY
2
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

AND INCREASE ALL MDA 60 FT, INCREASE LNAV CAT C AND D VISIBILITY AND CIRCLING CAT C VISIBILITY
1/4 MILE.

QUALITY
2
CHECKED

CITY AND STATE

LAKE VILLAGE, AR

ELEVATION: 125 TDZE: 125

AIRPORT NAME:

LAKE VILLAGE MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 1, ORIG

11 FEB 2010

SUP:

AMDT: NONE

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible][illegible]

QUALITY
Office

CITY AND STATE LAKE VILLAGE, AR	ELEVATION: 125 TDZE: 125 AIRPORT NAME: LAKE VILLAGE MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 1, ORIG 11 FEB 2010	SUP:
				AMDT: NONE
				DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

	1	2	3	4	5	6	7	8	9	0	1	2	3	
MSA	1	2	3	4	5	6	7	8	9	0	1	2	3	

SUSAP M32 K4SRW01 K4PG	0					18018001825					M			

QUALITY
CHECKED

CITY AND STATE
LAKE VILLAGE, AR

ELEVATION: 125 TDZE: 125
AIRPORT NAME:
LAKE VILLAGE MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 1, ORIG
11 FEB 2010

SUP:
AMDT: NONE
DATED: