

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.															
TERMINAL ROUTES										MISSED APPROACH									
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LNAV: RW31 CLIMB TO 3500 DIRECT OTSAY AND HOLD. ADDITIONAL FLIGHT DATA: HOLD NW, RT, 125.33 INBOUND. CHART FAS OBST: 984 TREE 361300N/0914338W CHART CIRCLING ICON. ZUKNA TO RW31: 3.00/40.1. CHART SHIRLEY B AND C MOA'S. CHART MOUNTAIN HOME ASOS.									
WIVOV (IF/IAF)		ZUKNA (TF) (FB) (RNP 1.00)		305.51 / 3.00				2400											
ZUKNA (FAF)		RW31 (MAP) (TF) (FO) (RNP 0.30)		305.48 / 4.97															
RW31 (MAP)		1181 MSL		305.48				3500											
1181 MSL		OTSAY (DF) (FO) (RNP 1.00)																	
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD SE WIVOV, RT, 305.51 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC: 305.48 FAF: ZUKNA DIST FAF TO MAP: 4.97 THLD: 4.97 4. MIN. ALT: WIVOV 3000, ZUKNA 2400 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR 8. MSA FROM: _____																MAG VAR: 0E		EPOCH YEAR: 2020	
MINIMUMS																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		<input checked="" type="checkbox"/> X							
CATEGORY =====>		A			B			C			D			E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA				
CIRCLING	1440	1	659	1440	1	659		NA			NA								
NOTES: CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: PROCEDURE NA AT NIGHT. CHART NOTE: USE MOUNTAIN HOME ALTIMETER SETTING; WHEN NOT RECEIVED, USE BATESVILLE ALTIMETER SETTING.																			
CITY AND STATE		ELEVATION: 781 TDZE:		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:									
HORSESHOE BEND, AR		AIRPORT NAME: HORSESHOE BEND		RNAV		RNAV (GPS)-A, ORIG 5 JANUARY 2017				AMDT: NONE									
										DATED									

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	216/30 CW 036/30 (NOPT)	WIVOV (IF/IAF) (FB)	3000
2.	036/30 CW 216/30	WIVOV (IAF) (FO)	3100

CITY AND STATE

HORSESHOE BEND, AR

ELEVATION: 781

TDZE:

AIRPORT NAME:

HORSESHOE BEND

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS)-A, ORIG

5 JANUARY 2017

SUP:

AMDT:

DATED:

QUALITY
4
CHECKED
NONE