

<b>RNAV - STANDARD</b> <b>INSTRUMENT APPROACH PROCEDURE</b> <b>TITLE 14 CFR PART 97.33</b>						Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
<b>TERMINAL ROUTES</b>										<b>MISSED APPROACH</b>					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		<b>LNAV: RW17</b>  <b>CLIMB TO 2000 DIRECT IRALE AND HOLD.</b>  <b>ADDITIONAL FLIGHT DATA:</b> <b>HOLD S, RT, 353.19 INBOUND.</b> <b>CHART FAS OBST: 105 TREE 300622N/0903447W</b> <b>CHART VDP AT 1.08 NM TO RW17.</b> <b>GASNE TO RW17: 3.00/50.</b> <b>CHART: CIRCLING ICON.</b>					
KBOOS (IF/IAF)		GASNE (FB)		173.17 / 6.00				1700							
GASNE (FAF)		NUDLE/1.50 NM TO RW17 (FB)		173.17 / 3.67											
NUDLE/1.50 NM TO RW17		RW17 (MAP) (FO)		173.17 / 1.50											
RW17 (MAP)		400 MSL		173.17				2000							
400 MSL		IRALE (FO)													

1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)									
2. HOLD N KBOOS, RT, 173.17 INBOUND, 1800 FT. IN LIEU OF PT (IAF)									
3. FAC: 173.17 FAF: GASNE DIST FAF TO MAP: 5.17 THLD: 5.17									
4. MIN. ALT: KBOOS 1800, GASNE 1700, NUDLE/1.50 NM TO RW17 520									
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____									
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____									
7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR									
8. MSA FROM: _____									

MAG VAR: 1W
EPOCH YEAR: 2020

MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD @						
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	400	1	394	400	1	394	400	1 1/8	394		NA				
CIRCLING	700	1	693	700	1	693	820	2 1/2	813		NA				

NOTES:

CHART NOTE: RWY 17 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.

CHART NOTE: DME/DME RNP-0.3 NA.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE LOUIS ARMSTRONG NEW ORLEANS INTL ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET, INCREASE LNAV CAT C VISIBILITY 1/4 SM.

CHART NOTE: VDP NA WHEN USING LOUIS ARMSTRONG NEW ORLEANS INTL ALTIMETER SETTING.

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

@ CAT C 900-2 1/2

CITY AND STATE		ELEVATION: 7 TDZE: 6		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:		SUP:	
RESERVE, LA		AIRPORT NAME:		RNAV		RNAV (GPS) RWY 17, AMDT 1A		AMDT: 1	
		PORT OF SOUTH LOUISIANA EXECUTIVE RGNL				5 JANUARY 2017		DATED 10/15/2015	

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
RNAV - STANDARD  
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	083/30 CW 263/30 (NOPT)	083/10 CW 263/10	2800
	083/10 CW 263/10	KBOOS (IF/IAF) (FB)	1800
2.	263/30 CW 083/30	263/10 CW 083/10	3100
	263/10 CW 083/10	KBOOS (IF/IAF) (FO)	1800

CITY AND STATE

RESERVE, LA

ELEVATION: 7

TDZE: 6

AIRPORT NAME:

PORT OF SOUTH LOUISIANA EXECUTIVE RGNL

FACILITY  
IDENTIFIER:  
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 17, AMDT 1A

5 JANUARY 2017

SUP:

AMDT:

DATED:

QUALITY  
4 1  
CHECKED  
10/15/2015

<b>U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION</b> <b>RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE</b> <b>FLIGHT STANDARDS SERVICES - TITLE 14 CFR PART 97.33</b>	Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.
--	--

ARINC SUMMARY - KAPS

ROUTES

TRANSITION	WPT SEQ	WPT NAME	LEG TYPE	FB/FO	RNP	MAG CRS	REC NAV	ANGLE	TURN DIR	CENTER FIX	TURN RADIUS	ALTITUDE DESCRIPTION & VALUE	SPEED LIMIT DESCRIPTION & VALUE	WPT DESCRIPTION CODE
KBOOS	010	KBOOS	HF	FO		173.2			R			AA 01800		EE A
	010	KBOOS	IF	FB								AA 01800		E I
	020	GASNE	TF	FB	1.0	173.2						AA 01700		E F
	021	NUDLE	TF	FB	0.3	173.2		3.00				AA 00520 GS 00532		E S
	030	RW17	TF	FO	0.3	173.2		3.00				AT 00054		GY M
	040		CA	FB		173.2						AA 00400		M
	050	IRALE	DF	FO	1.0							AA 02000		EY
	060	IRALE	HM	FO		353.2			R			AA 02000		EE

POINTS

POINT NAME	LATITUDE	LONGITUDE
GASNE	N301040.81	W0903549.68
IRALE	N295356.45	W0903311.21
KBOOS	N301638.30	W0903646.30
NUDLE	N300702.21	W0903515.11

RUNWAYS

RUNWAY	THRESHOLD LATITUDE	THRESHOLD LONGITUDE	THRESHOLD ELEVATION	PROCEDURE TCH
RW17	N300532.83	W0903500.99	00004	50.0

CITY AND STATE <b>RESERVE, LA</b>	ELEVATION: <b>7</b> <b>TDZE: 6</b> AIRPORT NAME: <b>PORT OF SOUTH LOUISIANA EXECUTIVE</b> <b>RGNL</b>	FACILITY IDENTIFIER:  <b>RNAV</b>	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: <b>RNAV (GPS) RWY 17, AMDT 1A</b>  5 JANUARY 2017	SUP: <span style="color: green; font-weight: bold;">QUALITY</span> <span style="color: green; font-weight: bold;">4</span> AMDT: <span style="color: green; font-weight: bold;">CHECKED</span> <span style="color: green; font-weight: bold;">1</span> DATED: <b>10/15/2015</b>
--------------------------------------	--	--	---	---