

**Federal Aviation
Administration**

Transmittal Letter 15-21

August 28, 2015

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
15-Oct-15	KY	Louisville	Louisville Intl- Standiford Field	5/6024	08/24/15	ILS OR LOC RWY 17R, Amdt 3D

AIRAC Date: 15 October 2015

FDC **5/6024** SDF IAP LOUISVILLE INTL-STANDIFORD FIELD, LOUISVILLE, KY. ILS OR LOC RWY 17R, AMDT 3D... VOYUK FIX MINIMUMS: CIRCLING CAT C MDA 1160/HAA 659, CAT D MDA 1400/HAA 899, VISIBILITY CAT D 3. CHART CIRCLING ICON. ALTERNATE MINIMUMS: ILS: CAT A/B 800-2, CAT C 800-2 1/2, CAT D 900-3. LOC: STANDARD, EXCEPT CAT C 800-2 1/2, CAT D 900-3. THIS IS ILS OR LOC RWY 17R, AMDT 3E. 1508201157-PERM