

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION LOC STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.25					Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.										
TERMINAL ROUTES					MISSED APPROACH										
FROM	TO	COURSE AND DISTANCE	ALTITUDE	MAP: 3.64 MILES AFTER KRING LOM OR AT (CFDRW) FIX											
RKA VOR/DME	KRING LOM	068.57 / 13.27	3900	CLIMBING RIGHT TURN TO 3900 DIRECT KRING LOM AND HOLD, CONTINUE CLIMB-IN-HOLD TO 3900.											
COOES INT	KRING LOM	167.66 / 11.54	3900												
					ADDITIONAL FLIGHT DATA: HOLD NE, RT, 237.16 INBOUND. CHART FAS OBST: 1940 TREE 423214N/0750237W KRING LOM TO RW24: 3.47/40. CHART IN PLANVIEW: (CFDRT) AT 423924.60N/0745333.80W										
1. PT <u>L</u> SIDE OF COURSE <u>057.16</u> OUTBOUND <u>3900</u> FT WITHIN <u>10</u> MILES OF <u>KRING LOM</u> (IAF)															
2.															
3. FAC <u>237.16</u> FAF <u>KRING LOM</u> DIST FAF TO MAP <u>3.64</u> THLD <u>4.64</u>															
4. MIN. ALT <u>KRING LOM 3500</u>															
8. MSA FROM: <u>KRING LOM 090-180 4700, 180-270 4100, 270-090 3700</u>															
					MAG VAR: 13W EPOCH YEAR: 2010										
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT					ALTERNATE: N A X										
CATEGORY ==>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-24	2220	1 1/4	462	2220	1 1/4	462		NA			NA				
CIRCLING	2340	1 1/4	577	2380	1 1/4	617		NA			NA				
NOTES: CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY. CHART NOTE: ADF REQUIRED. CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BINGHAMTON ALTIMETER SETTING AND (SEE FORM 8260-10)															
CITY AND STATE				ELEVATION: 1763 TDZE: 1758		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP			
ONEONTA, NY				AIRPORT NAME:		I-OZX		LOC RWY 24, AMDT 2B 12 DECEMBER 2013				AMDT 2A			
				ONEONTA MUNI								DATE 05/30/2013			

LOC STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.25

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

INCREASE ALL MDA 140 FEET.

CHART NOTE: LOCALIZER UNUSABLE 3.6 NM AFTER PASSING KRING LOM.

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.

CHART NOTE: PROCEDURE NA AT NIGHT.

QUALITY
CHECKED

CITY AND STATE

ONEONTA, NY

ELEVATION: 1763

TDZE: 1758

AIRPORT NAME:

ONEONTA MUNI

FACILITY
IDENTIFIER:

I-OZX

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

LOC RWY 24, AMDT 2B

12 DECEMBER 2013

SUP:

AMDT: 2A

DATED: 05/30/2013

FLIGHT STANDARDS SERVICES - FAR PART 97.25

ARINC PACKET - 424-18 - LOC

FLIGHT STANDARDS SERVICES - FAR PART 97.25

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibility which are in statute miles or in feet RVR.

[illegible]

QUALITY
4
CHECKED

CITY AND STATE ONEONTA, NY	ELEVATION: 1763 AIRPORT NAME: ONEONTA MUNI	TDZE: 1758 FACILITY IDENTIFIER: I-OZX	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: LOC RWY 24, AMDT 2B 12 DECEMBER 2013	SUP:
				AMDT: 2A
				DATED: 05/30/2013

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

LOC STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICES - FAR PART 97.25

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - LOC

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	COOES	COOES	010		IF		FB					
	COOES	KRING	020		TF		FB				AA 03900	
	COOES	KRING	030	IAF	PI	R	FB		012.2()	010.0	AA 03900	
	RKA	RKA	010		IF		FB					
	RKA	KRING	020		TF		FB				AA 03900	
	RKA	KRING	030	IAF	PI	R	FB		012.2()	010.0	AA 03900	
		CFDRT	010	FACF	IF		FB				AA 03900	
		KRING	020	FAF	CF		FB		237.0()	006.0	AA 03500	
		CFDRW	030	MAP	CF		FO		237.0()	003.6	AT 02159	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		237.2()		AA 02163	
	OZ	050		DF	R	FO				AA 03900	
	OZ	060		HM	R	FO		237.2()	T01.0	AA 03900	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	RKA	N422758.91	W0751421.51	N4227.982	W07514.359
	COOES	N424530.66	W0750553.87	N4245.511	W07505.898
	CFDRT	N423924.60	W0745333.80	N4239.410	W07453.563
	CFDRW	N423227.26	W0750236.20	N4232.454	W07502.603
	KRING	N423503.74	W0745909.99	N4235.062	W07459.167
	RW24	N423144.03	W0750332.54	N4231.734	W07503.542
	IOZX (LOC)	N423109.10	W0750418.39	N4231.152	W07504.307
	OZ	N423504.91	W0745911.61	N4235.082	W07459.194

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW24	01750	40

QUALITY
CHECKED

CITY AND STATE
ONEONTA, NYELEVATION: 1763 TDZE: 1758
AIRPORT NAME:
ONEONTA MUNIFACILITY
IDENTIFIER:
I-OZXPROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:
LOC RWY 24, AMDT 2B
12 DECEMBER 2013SUP:
AMDT: 2A
DATED: 05/30/2013