

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		ILS - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.29		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		ILS: DA LOC: 5.26 NM AFTER WAKEL INT					
ZUPDU INT (IF/IAF)		WAKEL INT		094.63 / 6.00 (I-PTK)				2700		CLIMB TO 1600 THEN CLIMBING RIGHT TURN TO 3000 DIRECT SVM VORTAC AND HOLD. ALTERNATE MA (DO NOT CHART): CLIMB TO 1600, THEN CLIMBING RIGHT TURN TO 2700 HEADING 250 FOR RADAR VECTORS. ADDITIONAL FLIGHT DATA: HOLD N, RT, 180.00 INBOUND. FAS OBST: 1369 AAO 423918N/0833139W. CHART CIRCLING ICON.					
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD W ZUPDU, LT, 094.63 INBOUND, 2700 FT. IN LIEU OF PT (IAF) 3. FAC: 094.63 FAF: WAKEL _____ DIST FAF TO MAP: 5.26 THLD: 5.26 4. MIN. ALT: ZUPDU 2700, WAKEL 2700 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: 883 6. MIN GS INCPT: 2700 GS ALT AT: WAKEL 2700 _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 45.2 8. MSA FROM: KPTK 2900															
										MAG VAR: 7W			EPOCH YEAR: 2020		
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A		ILS: STANDARD #		LOC: STANDARD @							
CATEGORY =====>		A		B		C		D		E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
S-ILS 09R**	1181	2400	200	1181	2400	200	1181	2400	200	1181	2400	200			
S-LOC 09R	1620	2400	639	1620	2400	639	1620	1 3/8	639	1620	1 3/8	639			
CIRCLING	1620	1	639	1620	1	639	1640	1 3/4	659	1640	2	659			
NOTES: CHART NOTE: CIRCLING RWY 09L, 36 NA AT NIGHT. CHART NOTE: **RVR 1800 AUTHORIZED WITH THE USE OF FD OR AP OR HUD TO DA, NA WHEN USING COLEMAN A YOUNG MUNI ALTIMETER SETTING. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE COLEMAN A YOUNG MUNI ALTIMETER SETTING (CONTINUED ON PAGE 2)															
CITY AND STATE PONTIAC, MI		ELEVATION: 981 TDZE: 981 AIRPORT NAME: OAKLAND COUNTY INTL		FACILITY IDENTIFIER: I-PTK		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: ILS OR LOC RWY 9R, AMDT 13 19 JULY 2018						SUP: AMDT: 12 DATED 08/27/2009			



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
ILS - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.29

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

AND INCREASE DA TO 1286 FEET AND ALL MDA 120 FEET, INCREASE S-LOC 9R CAT B VISIBILITY TO RVR 4000, CAT C/D VISIBILITY 3/8 SM, AND CIRCLING CAT B/C/D VISIBILITY 1/2 SM.

CHART NOTE: FOR INOPERATIVE MALSR, INCREASE S-LOC 9R CAT C/D VISIBILITY TO 1 3/4 SM.

CHART NOTE: FOR INOPERATIVE MALSR, WHEN USING COLEMAN A YOUNG ALTIMETER, INCREASE S-ILS 9R ALL CATS VISIBILITY TO RVR 4500, AND INCREASE S-LOC 9R CAT C/D VISIBILITY TO 2 SM.

EQUIPMENT REQUIREMENTS NOTE: RADAR REQUIRED FOR PROCEDURE ENTRY.

QUALITY
25
CHECKED

CITY AND STATE

PONTIAC, MI

ELEVATION: 981

TDZE: 981

AIRPORT NAME:

OAKLAND COUNTY INTL

FACILITY
IDENTIFIER:
I-PTK

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
ILS OR LOC RWY 9R, AMDT 13
19 JULY 2018

SUP:

AMDT: 12

DATED: 08/27/2009

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
ILS - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.29

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

QUALITY
25
CHECKED

CITY AND STATE
PONTIAC, MI

ELEVATION: 981 TDZE: 981
AIRPORT NAME:
OAKLAND COUNTY INTL

FACILITY
IDENTIFIER:
I-PTK

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
ILS OR LOC RWY 9R, AMDT 13
19 JULY 2018

SUP:
AMDT: **12**
DATED: **08/27/2009**