

TAKEOFF MINIMUMS AND TEXTUAL DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

Coordinated with:

ATA



ALPA



APA



AOPA



NBAA



OTHER (specify)



ZOA, CA AERO, AMGR

TAKEOFF MINIMUMS:

RWY 13: STANDARD

RWY 16: STANDARD

RWY 31: STANDARD

RWY 34: STANDARD

NOTE: 55' AGL POLE 530' FROM DEPARTURE END OF RUNWAY, 430
FEET RIGHT OF CENTERLINE.

TAKEOFF OBSTACLES:

RWY 34: 193' POLE (05-1656) 393137.00/1221307.00

TEXTUAL DP:

RWY 13: CLIMBING RIGHT TURN

RWY 16: CLIMB RWY HEADING

RWY 31, 34: CLIMBING LEFT TURN

ALL AIRCRAFT CLIMB DIRECT MXW VORTAC. AIRCRAFT DEPARTING
MXW VORTAC R-330 CW R-220, CLIMB ON COURSE. ALL OTHERS
CONTINUE CLIMB IN MXW HOLDING PATTERN (S, 350 INBOUND, LT)
TO DEPART MXW VORTAC 220 CW 290, 6500, 291 CW 330, 5500.

DP OBSTACLES:

THIS IS A CORRECTED COPY OF A PROCEDURE PUBLISHED IN TL 00-06.

City, State

WILLOWS, CA

Airport

WILLOWS-GLENN COUNTY

Effective Date

APR 20 2000

Amdt. No.

1