

TAKEOFF MINIMUMS AND TEXTUAL DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

(1) TAKEOFF MINIMUMS:

RWY 7, STANDARD WITH MINIMUM CLIMB OF 425 FEET PER NM TO 1400, OR 1000-3 FOR CLIMB IN VISUAL CONDITIONS.
RWY 25, STANDARD.

(2) DEPARTURE PROCEDURE:

RWY 7, CLIMBING RIGHT TURN. FOR CLIMB IN VISUAL CONDITIONS: CROSS LOMPOC AIRPORT EASTBOUND AT OR ABOVE 1200 MSL.
RWY 25, TURN RIGHT HEADING 130.

ALL AIRCRAFT CLIMB TO 6000 VIA GVO R-278 TO GVO VORTAC. AIRCRAFT DEPARTING GVO R-120 CW R-020 CLIMB ON COURSE, ALL OTHERS CLIMB IN GVO HOLDING PATTERN (NW, RT, 127 DEGREES INBOUND) TO DEPART GVO VORTAC AT OR ABOVE MEA FOR ROUTE OF FLIGHT.

(3) TAKEOFF OBSTACLE NOTES:

NOTE: RWY 7, TREES 3583 FEET FROM DER, 2.3 NM RIGHT OF CENTERLINE, 50 FEET AGL/889 FEET MSL. TREES 1.2 NM FROM DER, 2.2 NM RIGHT OF CENTERLINE, 50 FEET AGL/791 FEET MSL. TREES 1.6 NM FROM DER, 1.9 NM RIGHT OF CENTERLINE, 50 FEET AGL/743 FEET MSL.

(4) CONTROLLING OBSTACLES:

RWY 7, 889 MSL TREES 343723.38/1202655.68, 791 MSL TREES 343743.62/1202618.79, 743 MSL TREES 343801.35/1202543.23,
1079 MSL AAO 343849.06/1202313.23.

(5) City, State LOMPOC, CA	(6) Airport LOMPOC	(7) Effective Date JAN 20 2005	(8) Amdt. No. 2
--------------------------------------	------------------------------	--	---------------------------