

U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
TURTY	THREE	TURTY3.TURTY	TWO	06/27/2013	21 JUL 2016

TYPE: SID RNAV

DP ROUTE DESCRIPTION:

TAKEOFF RWY 20: CLIMB HEADING 199.13 TO 580, THEN CLIMB TO 6000 DIRECT IPIYA AND ON DEPICTED ROUTE TO TURTY.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

Transition Name	Transition Computer Codes	From FIX/NAVAID	To FIX/NAVAID	Course	Distance	MEA	MOCA	Crossing Altitudes/Fixes

PROCEDURAL DATA NOTES/TAKEOFF MINIMUMS:

NOTE: RNAV 1
NOTE: GPS REQUIRED

TAKEOFF MINIMUMS: RWY 2, NA-OBSTACLES.
RWY 20, STANDARD WITH MINIMUM CLIMB OF 422 FT PER NM TO 2500.

TAKEOFF OBSTACLES NOTES:

RWY 20, TREES BEGINNING 4811' FROM DER, 1716' RIGHT OF CENTERLINE, UP TO 158' AGL/557' MSL. TREES 5964' FROM DER, 1370' LEFT OF CENTERLINE. UP TO 158' AGL/357' MSL.

CONTROLLING OBSTACLES:

RWY 20: 357 MSL TREE 553332.00N/1330548.00W, 3148 MSL AAO 554124.40N/1331020.10W.

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:

CHART: V311
REFERENCE MAGVAR: PAKW 20E, EPOCH YR: 2015
DME/DME ASSESSMENT: NOT CONDUCTED.
CHART: TOP ALTITUDE: ASSIGNED BY ATC

QUALITY
15
CHECKED

U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
TURTY	THREE	TURTY3.TURTY	TWO	06/27/2013	21 JUL 2016

AIRPORTS SERVED:

KLAWOCK

KLAWOCK, AK

COMMUNICATIONS:

ASOS; AKW /PAKW; DEP CON; ZAN, CTAF: AKW/PAKW.

FIXES AND/OR NAVAIDS:

IPAYA, HUPDA, PUYIP, NESYI, TURTY

REMARKS:

U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
TURTY	THREE	TURTY3.TURTY	TWO	06/27/2013	21 JUL 2016

REQUIRED EFFECTIVE DATE:

ROUTINE

COORDINATED WITH:

CHANGES:

ADDED: CHART: TOP ALTITUDE: ASSIGNED BY ATC

REASONS:

ATC REQUEST



DEPARTURE (DATA RECORD)

DP Name		Number	DP Computer Code			Superseded Number		Dated	Effective Date
TURTY		THREE	TURTY3.TURTY			TWO		06/27/2013	21 JUL 2016
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS
RW20 (AER)	553504.35N/1330406.14W	N	-	-	-	-			
580 MSL	-	-	-	VA	219.13				CG 422 FT/NM TO 2500
IPIYA	553326.57N/1330626.47W	Y	FB	DF	-				
HUPDA	552955.03N/1331129.19W	Y	FB	TF	219.10	4.55			
PUYIP	553245.22N/1332244.48W	Y	FB	TF	294.03	7.00			
NESYI	553939.37N/1332050.01W	Y	FB	TF	008.88	7.00			
TURTY	554826.84N/1330858.14W	Y	FB	TF	037.21	11.07			