

TAKEOFF MINIMUMS AND TEXTUAL DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

(1) TAKEOFF MINIMUMS:

RWY 2, 1800-2 OR STANDARD WITH MINIMUM CLIMB OF 280 FT PER NM TO 6900.

RWY 7, 12, 900-2 OR STANDARD WITH MINIMUM CLIMB OF 220 FT PER NM TO 6200.

RWY 20, 25, 30, STANDARD.

(2) TEXTUAL DP:

RWYS 2, 30, LEFT TURN.

RWYS 7, 12, 20, RIGHT TURN.

RWY 25, CLIMB RUNWAY HEADING.

ALL AIRCRAFT CLIMB DIRECT LWT VORTAC. CONTINUE CLIMB IN HOLDING PATTERN (WEST, RIGHT TURNS, 094 INBOUND) TO MEA FOR ROUTE OF FLIGHT.

(3) TAKEOFF OBSTACLES:

RWYS 2, 6127' TERRAIN 470827/1091607

RWYS 7, 12, 5680' TERRAIN 465417/1092320

(4) OBSTACLES:

ALL RWYS, 4979 TREES 465806/1092612

(5) City, State

LEWISTOWN, MT

(6) Airport

LEWISTOWN MUNI

(7) Effective Date
6 SEP 01

(8) Amdt. No.
3