

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - FAR PART 97.23					Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.										
TERMINAL ROUTES					MISSED APPROACH										
FROM	TO	COURSE AND DISTANCE	ALTITUDE	MAP: RID VORTAC CLIMB TO 2700 THEN RIGHT TURN DIRECT RID VORTAC AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SW, RT, 066.00 INBOUND. CHART FAS OBST: 1226 TREE 394437N/0844958W CHART 1292 TOWER 394409N/0845616W. CHART VDP AT 1.57 DME; DISTANCE VDP TO THLD 1.07 MILES. CHART TDZE: 1137 FAC CROSSES RWY C/L EXTENDED 2516 FROM THLD.											
1. PT <u> L </u> SIDE OF COURSE <u> 246.00 </u> OUTBOUND <u> 2700 </u> FT WITHIN <u> 10 </u> MILES OF <u> RID VORTAC </u> (IAF) 2. _____ 3. FAC <u> 066.00 </u> FAF _____ DIST FAF TO MAP _____ THLD _____ 4. MIN. ALT <u> BOTKE/2.60 DME 1660* * 1760 WHEN USING JAMES M COX DAYTON INTL ALTIMETER SETTING </u> 8. MSA FROM: <u> RID VORTAC 360-180 3100, 180-360 2600 </u>					MAG VAR: 3W EPOCH YEAR: 1985										
MINIMUMS															
TAKEOFF:	STANDARD	<input checked="" type="checkbox"/>	SEE FAA FORM 8260-15A FOR THIS AIRPORT			ALTERNATE:	NA	<input checked="" type="checkbox"/>							
CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-6	1660	1	523	1660	1	523	1660	1 1/2	523	1660	1 3/4	523			
CIRCLING	1660	1	520	1660	1	520	1660	1 1/2	520	1700	2	560			
BOTKE FIX MINIMUMS															
S-6	1500	1	363	1500	1	363	1500	1	363	1500	1 1/4	363			
CIRCLING	1600	1	460	1600	1	460	1600	1 1/2	460	1700	2	560			
NOTES: CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE JAMES M COX DAYTON INTL ALTIMETER SETTING AND INCREASE ALL MDA 100 FEET. INCREASE S-6 CAT C, D AND CIRCLING CAT C VISIBILITY 1/4 MILE. INCREASE BOTKE FIX MINIMUMS S-6 CAT C, D VISIBILITY 1/4 MILE. CHART NOTE: VDP NA WHEN USING JAMES M COX DAYTON INTL ALTIMETER SETTING.															
CITY AND STATE		ELEVATION: 1140 TDZE: 1137		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP VOR OR GPS RWY					
RICHMOND, IN		AIRPORT NAME:		RID		VOR RWY 6, AMDT 12				6					
		RICHMOND MUNI				02 JUL 2009				11B					
										DATE					