

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: OSH VORTAC						
										CLIMBING LEFT TURN TO 3000 ON OSH VORTAC R-111.18 TO LEWKO INT/OSH 15.07 DME AND HOLD.						
										ADDITIONAL FLIGHT DATA: HOLD W, LT, 111.18 INBOUND. CHART FAS OBST: 950 TWR 440117N/0883235W CHART VDP AT 1.05 DME; DISTANCE VDP TO THLD 1.33 MILES. WOMEN TO RW18: 2.92/47. FAC CROSSES RWY C/L EXTENDED 821 FROM THLD.						
1. PT <u>L</u> SIDE OF COURSE <u>005.99</u> OUTBOUND <u>2600</u> FT WITHIN <u>10</u> MILES OF <u>OSH VORTAC</u> (IAF)										MAG VAR: 2E EPOCH YEAR: 1965						
2.																
3. FAC <u>185.99</u> FAF DIST FAF TO MAP THLD																
4. MIN. ALT <u>WOMEN/OSH 1.80 DME 1480*</u>																
8. MSA FROM: <u>OSH VORTAC 2700</u>																
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @						
CATEGORY ==>		A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
S-18	1480	1	690	1480	1	690	1480	2	690	1480	2	690				
CIRCLING	1480	1	672	1480	1	672	1480	2	672	1480	2 1/4	672				
WOMEN FIX MINIMUMS																
S-18	1260	1	470	1260	1	470	1260	1 3/8	470	1260	1 3/8	470				
CIRCLING	1280	1	472	1300	1	492	1360	1 1/2	552	1440	2	632				
NOTES: CHART NOTE: CIRCLING TO RWY 5, 23, AND 31 NA AT NIGHT. * 1520 WHEN USING FOND DU LAC ALTIMETER SETTING. CHART NOTE: VDP NA WITH FOND DU LAC COUNTY ALTIMETER SETTING. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE FOND DU LAC ALTIMETER SETTING AND (SEE FORM 8260-10)																
CITY AND STATE OSH KOSH, WI		ELEVATION: 808 THRE: 790 AIRPORT NAME: WITTMAN RGNL		FACILITY IDENTIFIER: OSH		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 18, AMDT 8 22 AUGUST 2013				SUP						
										AMDT 7						
										DATE 06/05/2008						

@ CAT D 800-2 1/4
 @ NA WHEN LOCAL WEATHER NOT AVAILABLE.

QUALITY
 6
 CHECKED

VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

INCREASE ALL MDA 40 FEET; INCREASE WOMEN FIX MINIMUMS CIRCLING CAT D VISIBILITY 1/4 MILE.

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.

QUALITY
6
CHECKED

CITY AND STATE

OSHKOSH, WI

ELEVATION: 808

THRE: 790

AIRPORT NAME:

WITTMAN RGNL

FACILITY
IDENTIFIER:

OSH

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR RWY 18, AMDT 8

22 AUGUST 2013

SUP:

AMDT:

7

DATED:

06/05/2008