

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
NDB STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.27

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	MAP: 5.97 MILES AFTER OA LOM
WALLO INT	ELLAS LOM	128.69 / 14.81	2100	CLIMBING LEFT TURN TO 2100 DIRECT OA LOM AND HOLD.
BEULA INT	ELLAS LOM	190.52 / 11.04	2100	
KROVE INT	ELLAS LOM	240.90 / 27.69	2600	
HELNA INT (IAF)	ELLAS LOM (NOPT)	064.75 / 12.85	2100	
GOLLA INT (IAF)	ELLAS LOM (NOPT)	037.70 / 8.54	2100	
				ADDITIONAL FLIGHT DATA: HOLD SW, LT, 052.03 INBOUND. CHART FAS OBST: 200 TREE 344725N/0773920W OA LOM TO RW05: 3.08/55.

1. PT R SIDE OF COURSE 232.03 OUTBOUND 2100 FT WITHIN 10 MILES OF ELLAS LOM (IAF)
2. _____
3. FAC 052.03 FAF ELLAS LOM DIST FAF TO MAP 5.97 THLD 5.97
4. MIN. ALT OA LOM 2100
8. MSA FROM: OA LOM 3100

MAG VAR: 8W

EPOCH YEAR: 1990

MINIMUMS

TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A	X				
CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-5	500	3/4	410	500	3/4	410	500	3/4	410	500	1	410			
CIRCLING	500	1	406	560	1	466	560	1 1/2	466	660	2	566			

NOTES:

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE WILMINGTON ALTIMETER SETTING AND INCREASE ALL MDAS 100 FEET AND S-5 VISIBILITY CATS C AND D 1/4 MILE.

CITY AND STATE JACKSONVILLE, NC	ELEVATION: 94 TDZE: 90 AIRPORT NAME: ALBERT J ELLIS	FACILITY IDENTIFIER: OA	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: NDB RWY 5, AMDT 8 25 SEP 2008	SUP NDB OR GPS RWY 5
				AMDT 7B
				DATE 11/23/2006