

**Federal Aviation
Administration**

Transmittal Letter 08-24

OCTOBER 17, 2008

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DAT	SUBJECT
10/10/08	SC	Greenwood	Greenwood County	8/3529		VOR OR GPS RWY 9, Amdt 13

AIRAC Date: 10 OCTOBER 2008

FDC 8/3529 GRD FI/P GREENWOOD COUNTY, GREENWOOD, SC. VOR OR GPS RWY 9, AMDT 13...CHANGE DME MINIMUMS TO FOCRU FIX MINIMUMS. CHANGE (FOCRU) CNF FIX TO FOCRU/GRD 2.00 DME. DELETE: ALTERNATE MINIMUMS NA. ALTERNATE MINIMUMS: STANDARD EXCEPT NA WHEN LOCAL WEATHER NOT AVAILABLE. DELETE NOTE: OBTAIN LOCAL ALTIMETER SETTING ON CTAF; WHEN NOT RECEIVED, USE ANDERSON ALTIMETER SETTING AND INCREASE ALL MDAS 100 FEET AND CAT C VISIBILITIES 1/4 MILE, CAT D VISIBILITIES 1/2 MILE. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ANDERSON ALTIMETER SETTING AND INCREASE ALL MDA 100 FEET AND S-9 AND FOCRU FIX MINIMUMS CATS C AND D VISIBILITY 1/4 MILE, CIRCLING CAT D VISIBILITY 1/2 MILE. THIS IS VOR OR GPS RWY 9, AMDT 13A.