

U.S. Department of Transportation
Federal Aviation Administration

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
FELAK WP (IAF)	BIKAY WP(TF) (FB) (NOPT)	085.14/5.00	3000	LNAV: RW35
WAGOM WP (IAF)	BIKAY WP(TF) (FB) (NOPT)	265.28/5.00	3000	CLIMBING LEFT TURN TO 3000 DIRECT BIKAY WP AND HOLD
BIKAY WP (IF/IAF)	LIFDI WP (TF) (FB)	355.21/6.00	2600	
RW35 (MAP)	1420 MSL (CA)	355.19		ADDITIONAL FLIGHT DATA: FAS OBST:1059 TREE 385242/835243 LIFDI WP TO RW35: 3.03/40 FINAL SEGMENT (TF) CHART BUCKEYE MOA
1420 MSL	BIKAY WP (DF) (FO)		3000	

1. PT NA SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. HOLD S BIKAY WP, RT, 355.21 INBOUND, 3000 FT. IN LIEU OF PT (IAF)
3. FAC: 355.19 FAF: LIFDI WP DIST FAF TO MAP: 5.00 THLD: 5.00
4. MIN. ALT: BIKAY WP 3000, LIFDI WP 2600
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
6. MIN GS INCPT: GS ALT AT: OM: MM: IM:
7. GS ANGLE: TCH: 34:1 IS CLEAR
8. MSA FROM:

MAG VAR: 5W

EPOCH YEAR: 00

MINIMUMS

TAKEOFF:		STANDARD	X	SEE FAA FORM	8260-15A	FOR THIS AIRPORT	ALTERNATE: N A	X								
CATEGORY		A			B			C			D			E		
		DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA
LNAV	MDA	1420	1	462	1420	1	462	1420	1 1/4	462		NA				
CIRCLING		1460	1	502	1580	1	622	1600	1 3/4	642		NA				

NOTES: GPS OR RNP-0.3 REQUIRED. DME/DME RNP-0.3 NA.
USE CINCINNATI/NORTHERN KENTUCKY INTL, KY ALTIMETER SETTING.

CITY AND STATE	ELEVATION: 958 TDZE: 958	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: APR 15 2004 RNAV (GPS) RWY 35, ORIG	SUP: NONE DATE
GEORGETOWN, OH	AIRPORT NAME: BROWN COUNTY			

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV **STANDARD INSTRUMENT APPROACH PROCEDURE**
FLIGHT STANDARDS SERVICES TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA:

FROM	TO	ALTITUDE
1. 265/30 CW 085/30	BIKAY WP (IF/AF) (NOPT)	3000
2. 085/30 CW 175/30	FELAK WP (IAF)	3000
3. 175/30 CW 265/30	WAGOM WP (IAF)	3000

CITY AND STATE

GEORGETOWN, OH

ELEVATION:

958 TDZE:

958

AIRPORT NAME:

BROWN COUNTY

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:

APR 15 2004
RNAV (GPS) RWY 35, ORIG

SUP:

AMDT: NONE

DATED: