

| | | | | | |
|---|----------------------------|--|------------------|--|-----|
| US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION | | RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33 | | Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR. | |
| TERMINAL ROUTES | | | | MISSED APPROACH | |
| FROM | TO | COURSE AND DISTANCE | ALTITUDE | LP: RW12 LNAV: RW12 CLIMB TO 3000 DIRECT WOVLA AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SE, RT, 299.61 INBOUND. CHART FAS OBST: 1375 TOWER 424500N/0943931W WAAS CHANNEL # 58223 REFERENCE PATH ID: W12A CHART ALGONA AWOS-3 OYIBU TO RW12: 3.00/45 LTP HAE: 344.6 M | |
| EVIFI (IF/IAF) | OYIBU (FB) | 119.30 / 7.00 | 2800 | | |
| OYIBU (FAF) | HUMIB/1.80 NM TO RW12 (FB) | 119.39 / 3.00 | | | |
| HUMIB/1.80 NM TO RW12 | RW12 (MAP) (FO) | 119.43 / 1.80 | | | |
| RW12 / RW12 (MAP) | 1626 MSL | 119.43 | 3000 | | |
| 1626 MSL | WOVLA (FO) | | | | |
| 1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD NW EVIFI, RT, 119.30 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC: <u>119.39</u> FAF: <u>OYIBU</u> DIST FAF TO MAP: <u>4.80</u> THLD: <u>4.80</u> 4. MIN. ALT: <u>EVIFI 3000, OYIBU 2800, HUMIB/1.80 NM TO RW12 1840</u> 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u> </u> TCH: <u>34:1</u> IS NOT CLEAR 8. MSA FROM: <u> </u> | | | | | |
| | | | | MAG VAR: 2E EPOCH YEAR: 2010 | |
| MINIMUMS | | | | | |
| TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT | | | ALTERNATE: N A X | | |
| CATEGORY =====> | A | | B | | C |
| | DH/MDA | VIS | HAT/HAA | DH/MDA | VIS |
| LP MDA | 1740 | 1 | 514 | 1740 | 1 |
| LNAV MDA | 1740 | 1 | 514 | 1740 | 1 |
| CIRCLING | 1800 | 1 | 574 | 1940 | 1 |
| | | | | | |
| | | | | | |
| | | | | | |
| NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT. CHART NOTE: USE ALGONA ALTIMETER SETTING; WHEN NOT RECEIVED, USE FORT DODGE ALTIMETER SETTING AND INCREASE ALL MDA 20 FT AND INCREASE LP/LNAV CAT C VISIBILITY TO 1 1/2 MILE. | | | | | |
| CITY AND STATE POCAHONTAS, IA | | ELEVATION: 1226 THRE: 1226 AIRPORT NAME: POCAHONTAS MUNI | | FACILITY IDENTIFIER: RNAV | |
| | | | | PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 12, ORIG 25 AUG 2011 | |
| | | | | SUP: AMDT: NONE DATED | |

QUALITY
 &
 CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

| | FROM | TO | ALT |
|----|-------------------------|---------------------|------|
| 1. | 029/30 CW 209/30 (NOPT) | EVIF1 (IF/IAF) (FB) | 3000 |
| 2. | 209/30 CW 029/30 | EVIF1 (IAF) (FO) | 3400 |

QUALITY
1
CHECKED

CITY AND STATE
POCAHONTAS, IA

ELEVATION: 1226 THRE: 1226
 AIRPORT NAME:
POCAHONTAS MUNI

FACILITY
 IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 12, ORIG
25 AUG 2011

SUP:
 AMDT: **NONE**
 DATED:

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0
SBAS SERVICE PROVIDER IDENTIFIER 0
AIRPORT IDENTIFIER KPOH
RUNWAY RW12
APPROACH PERFORMANCE DESIGNATOR 0
ROUTE INDICATOR
REFERENCE PATH DATA SELECTOR 0
REFERENCE PATH IDENTIFIER (APPROACH ID) W12A
LTP/FTP LATITUDE 424444.5565N
LTP/FTP LONGITUDE 0943916.4090W
LTP/FTP ELLIPSOIDAL HEIGHT +03446
FPAP LATITUDE 424358.0500N
FPAP LONGITUDE 0943733.2700W
THRESHOLD CROSSING HEIGHT (TCH) 00045.0
TCH UNITS SELECTOR (METERS OR FEET USED) F
GLIDEPATH ANGLE (GPA) 03.00
COURSE WIDTH AT THRESHOLD 106.75
LENGTH OFFSET 1504
HORIZONTAL ALERT LIMIT (HAL) 40.0
VERTICAL ALERT LIMIT (VAL) 0.0

CRC REMAINDER

11202284

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K3
LTP ORTHOMETRIC HEIGHT +03735
FPAP ORTHOMETRIC HEIGHT +03735

QUALITY
A
CHECKED

| | | | | |
|----------------------------------|--|---------------------------------|--|------------------------------|
| CITY AND STATE POCAHONTAS, IA | ELEVATION: 1226 THRE: 1226 AIRPORT NAME: POCAHONTAS MUNI | FACILITY IDENTIFIER: RNAV | PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 12, ORIG 25 AUG 2011 | SUP: AMDT: NONE DATED: |
|----------------------------------|--|---------------------------------|--|------------------------------|

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
A
CHECKED

| | | | | |
|----------------------------------|---|-------------------------------------|--|------------|
| CITY AND STATE POCAHONTAS, IA | ELEVATION: 1226 THRE: 1226 AIRPORT NAME: POCAHONTAS MUNI | FACILITY IDENTIFIER: RNAV | PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 12, ORIG 25 AUG 2011 | SUP: |
| | | | | AMDT: NONE |
| | | | | DATED: |