



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
**RNAV (RNP) - STANDARD,  
 INSTRUMENT APPROACH PROCEDURE, - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
YUSGU (FAF)	RW19 (MAP) (TF) (FO)	186.53 / 4.71	
RW19 (MAP)	ZEKUG (TF) (FB) (RNP 1.00)	186.51 / 4.25	
ZEKUG	KICNE (TF) (FO) (RNP 1.00)	193.18 / 22.04	14000

NOTES, (CONT.):

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON DNW VOR/DME AIRWAY RADIALS 219 CW 267.  
 CHART PLANVIEW NOTE AT TOCUD: (RNP 0.50).  
 CHART PLANVIEW NOTE AT DNW VOR/DME: (RNP 0.50).  
 CHART NOTE: FOR INOPERATIVE MALS, INCREASE \*RNP 0.30 VISIBILITY ALL CATS TO 1 3/4.

QUALITY  
2  
[Signature]

CITY AND STATE JACKSON, WY	ELEVATION: 6451	THRE: 6451	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (RNP) Y RWY 19, AMDT 1 7 MARCH 2013	SUP: RNAV (RNP) Z RWY 19
	AIRPORT NAME: JACKSON HOLE				AMDT: ORIG-B
					DATED: 06/30/2011

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	KJACK1FH19-Y	ATOCUD	010	TOCUDK1EA0E	IF					18000		A	FS
SUSAP	KJACK1FH19-Y	ATOCUD	020	DNW K1D 0V	A 010TF			+ 12900				A	FS
SUSAP	KJACK1FH19-Y	ATOCUD	030	ZIBIVK1EA0EE	B 010TF			+ 11000				A	FS
SUSAP	KJACK1FH19-Y	H	010	ZIBIVK1EA0E	I IF			+ 11000	18000			A	FS
SUSAP	KJACK1FH19-Y	H	011	ZOSUVK1EA0E	051TF			+ 09800				A	FS
SUSAP	KJACK1FH19-Y	H	012	WOMRUK1EA0E	051TF			+ 08700				A	FS
SUSAP	KJACK1FH19-Y	H	020	YUSGUK1EA1E	F 051TF			+ 08000			RW19	K1PGA	FS
SUSAP	KJACK1FH19-Y	H	020	YUSGUK1EA2W				A031					FS
SUSAP	KJACK1FH19-Y	H	030	RW19 K1PG0GY	M 031TF			06500		-300		A	FS
SUSAP	KJACK1FH19-Y	H	040	ZEKUGK1EA0E	M 010TF							A	FS
SUSAP	KJACK1FH19-Y	H	050	KICNEK1EA0EY	010TF			+ 14000				A	FS
SUSAP	KJACK1FH19-Y	H	060	KICNEK1EA0EE	R HM		01260080	+ 14000				A	FS

[illegible]

MSA 1 2 3 4 5 6 7 8 9 0 1 2

CITY AND STATE <b>JACKSON, WY</b>	ELEVATION: <b>6451</b> THRE: <b>6451</b> AIRPORT NAME: <b>JACKSON HOLE</b>	FACILITY IDENTIFIER:  <b>RNAV</b>	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: <b>RNAV (RNP) Y RWY 19, AMDT 1</b>  7 MARCH 2013	SUP: <b>RNAV (RNP) Z RWY</b>
				<b>19</b>
				AMDT: <b>ORIG B</b>
				DATED: <b>06/30/2011</b>

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
**RNAV (RNP) STANDARD INSTRUMENT APPROACH PROCEDURE**  
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

SUSAP KJACK1SRW19 K1PG

0 18018015025

M



CITY AND STATE  
JACKSON, WY

ELEVATION: 6451 THRE: 6451  
AIRPORT NAME:  
JACKSON HOLE

FACILITY  
IDENTIFIER:  
  
RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:  
RNAV (RNP) Y RWY 19, AMDT 1  
7 MARCH 2013

SUP: RNAV (RNP) Z RWY  
19  
AMDT: ORIG B  
DATED: 06/30/2011

**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**RNAV (RNP) STANDARD INSTRUMENT APPROACH PROCEDURE**  
**FLIGHT STANDARDS SERVICES - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (RNP)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	TOCUD	TOCUD	010		IF		FB					
	TOCUD	DNW	020	IAF	TF		FB	1.0			AA 12900	
	TOCUD	ZIBIV	030		TF		FB	1.0			AA 11000	
		ZIBIV	010	FACF	IF		FB				AA 11000	
		ZOSUV	011		TF		FB	0.5			AA 09800	
		WOMRU	012		TF		FB	0.5			AA 08700	
		YUSGU	020	PAF	TF		FB	0.5			AA 08000	
		RW19	030	MAP	TF		FO	0.3			AT 06500	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	ZEKUG	040		TF		FB	1.0				
	KICNE	050		TF		FO	1.0			AA 14000	
	KICNE	060		HM	R	FO		012.6 (025.6T)	008.0	AA 14000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	DNW	N434941.80	W1102007.71	N4349.697	W11020.129
	KICNE	N431307.69	W1105916.71	N4313.128	W11059.279
	TOCUD	N440352.75	W1100818.40	N4403.879	W11008.307
	WOMRU	N434354.16	W1104037.12	N4343.903	W11040.619
	YUSGU	N434122.02	W1104151.57	N4341.367	W11041.860
	ZEKUG	N433255.31	W1104558.73	N4332.922	W11045.979
	ZIBIV	N434851.78	W1103152.55	N4348.863	W11031.876
	ZOSUV	N434702.37	W1103711.60	N4347.040	W11037.193
	RW19	N433655.73	W1104401.60	N4336.929	W11044.027

RUNWAY DATA	RWY	THRESHOLD	TCH
		ELEVATION	
	RW19	06451	50

QUALITY  
4

CITY AND STATE <b>JACKSON, WY</b>	ELEVATION: <b>6451</b>	THRE: <b>6451</b>	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: <b>RNAV (RNP) Y RWY 19, AMDT 1</b> 7 MARCH 2013	SUP: <b>RNAV (RNP) Z RWY 19</b>
	AIRPORT NAME: <b>JACKSON HOLE</b>				AMDT: <b>ORIG B</b>
					DATED: <b>06/30/2011</b>