

U.S. Department
of Transportation

800 Independence Ave., S.W.
Washington, D.C. 20591

**Federal Aviation
Administration**

Transmittal Letter 16-07

February 12, 2016

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
31-Mar-16	WY	Casper	Casper/Natrona County Intl	5/0128	01/26/16	ILS OR LOC RWY 3, Amdt 7

EFFECTIVE 31 MARCH 2016

FDC **5/0128** CPR IAP CASPER/NATRONA COUNTY INTL, CASPER, WY. ILS OR LOC RWY 3, AMDT 7... DELETE THRE 5324 CHART TDZE 5328. CHANGE APT ELEV FROM 5350 TO 5344. CIRCLING HAA 876 ALL CATS. S-LOC 3 HAT 892 ALL CATS. MAMUE FIX MINIMUMS S-LOC 3 HAT 412 ALL CATS.. MAMUE FIX MINIMUMS CIRCLING HAA CAT A 396, CAT B/C 456, CAT D 556. CHANGE ALTIMETER SETTING NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE DOUGLAS ALTIMETER SETTING; INCREASE DA TO 5697 FEET AND ALL MDAS 180 FEET, INCREASE S-ILS VISIBILITY ALL CATS 1/4 MILE AND S-LOC VISIBILITY CATS B, C, AND D 1/2 MILE, INCREASE CIRCLING VISIBILITY CATS B,C, AND D 1/2 MILE.. S-ILS 3 DA 5528 ALL CATS. THIS IS ILS OR LOC RWY 3, AMDT 7A. 1512211651-PERM