

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE		ALTITUDE		LP: RW04 LNAV: RW04							
WIKEM (IAF)		IGOTE (NOPT) (TF) (FB) (RNP 1.00)		134.71 / 8.00		3300		CLIMB TO 2500 DIRECT WEVOB AND HOLD.							
HETOS (IAF)		IGOTE (NOPT) (TF) (FB) (RNP 1.00)		314.83 / 8.00		3300									
IGOTE (IF/IAF)		PILAU (TF) (FB) (RNP 1.00)		044.77 / 10.00		1900									
PILAU (FAF)		SEPIC/2.30 NM TO RW04 (TF) (FB) (RNP 0.30)		044.83 / 2.75											
SEPIC/2.30 NM TO RW04		RW04 (MAP) (TF) (FO) (RNP 0.30)		044.83 / 2.30				ADDITIONAL FLIGHT DATA: HOLD NE, RT, 224.91 INBOUND. CHART FAS OBST: 364 TREE 305324N/0835344W CHART FAS OBST: 388 TREE 305254N/0835443W CHART: 695 TOWER 305010N/0835751W WAAS CHANNEL # 56640 REFERENCE PATH ID: W04A CHART CIRCLING ICON. PILAU TO RW04: 3.00/54. LTP HAE: 45 M							
(SEE FORM 8260-10)															
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)										MAG VAR: 5W EPOCH YEAR: 2020					
2. HOLD SW IGOTE, RT, 044.77 INBOUND, 3300 FT. IN LIEU OF PT (IAF)															
3. FAC: 044.83 FAF: PILAU DIST FAF TO MAP: 5.05 THLD: 5.05															
4. MIN. ALT: IGOTE 3300, PILAU 1900, SEPIC/2.30 NM TO RW04 1020															
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____															
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____															
7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR															
8. MSA FROM: _____															
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A		STANDARD @							
CATEGORY =====>		A		B		C		D		E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LP MDA	620	1	378	620	1	378	620	1	378	620	1	378			
LNAV MDA	640	1	398	640	1	398	640	1 1/8	398	640	1 1/8	398			
CIRCLING	700	1	436	800	1	536	900	1 3/4	636	1040	2 1/2	776			
NOTES: CHART NOTE: RWY 4 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: STRAIGHT-IN RWY 4 NA AT NIGHT, CIRCLING RWY 4 NA AT NIGHT. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE VALDOSTA ALTIMETER SETTING: INCREASE ALL MDAS 100 FEET AND ALL CAT C AND D VISIBILITIES 3/8 SM.															
CITY AND STATE THOMASVILLE, GA		ELEVATION: 264 TDZE: 242 AIRPORT NAME: THOMASVILLE RGNL		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 4, ORIG 17 AUGUST 2017						SUP: AMDT: NONE DATED			



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW04 (MAP)	620 MSL (CA)	044.83	

620 MSL	WEVOB (DF) (FO) (RNP 1.00)	2500
---------	----------------------------	------

TAA

	FROM	TO	ALT
1.	315/30 CW 135/30 (NOPT)	IGOTE (IF/IAF) (FB)	3300
2.	135/30 CW 225/30	WIKEM (IAF) (FB)	3300
3.	225/30 CW 315/30	HETOS (IAF) (FB)	3300



CITY AND STATE THOMASVILLE, GA	ELEVATION: 264	TDZE: 242	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 4, ORIG 17 AUGUST 2017	SUP:
	AIRPORT NAME:				AMDT: NONE
	THOMASVILLE RGNL				DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KTVI
RUNWAY	RW04
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W04A
LTP/FTP LATITUDE	305342.7800N
LTP/FTP LONGITUDE	0835315.1625W
LTP/FTP ELLIPSOIDAL HEIGHT	+00450
FPAP LATITUDE	305451.3230N
FPAP LONGITUDE	0835208.7765W
THRESHOLD CROSSING HEIGHT (TCH)	00053.9
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1080
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	0.0
 <u>CRC REMAINDER</u>	 D535DF20

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+00726
FPAP ORTHOMETRIC HEIGHT	+00726

QUALITY
16
CHECKED

CITY AND STATE THOMASVILLE, GA	ELEVATION: 264 AIRPORT NAME: THOMASVILLE RGNL	TDZE: 242 THOMASVILLE RGNL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 4, ORIG 17 AUGUST 2017	SUP:
					AMDT: NONE
					DATED: