

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: MHE VOR/DME						
										CLIMB TO 2900 THEN CLIMBING RIGHT TURN TO 3000 DIRECT MHE VOR/DME AND HOLD.						
										ADDITIONAL FLIGHT DATA: HOLD SE, RT, 324.78 INBOUND. CHART FAS OBST: 1492 TWR 434259N/0980113W CHART 1916 TOWER 434122N/0980030W. CHART VDP AT 1.79 DME DISTANCE VDP TO THLD 1.24 MILES. CHART CIRCLING ICON. FAC CROSSES RWY C/L EXTENDED 2988 FT FROM THLD.						
1. PT <u> L </u> SIDE OF COURSE <u> 144.78 </u> OUTBOUND <u> 3000 </u> FT WITHIN <u> 10 </u> MILES OF <u> MHE VOR/DME </u> (IAF) 2. _____ 3. FAC <u> 324.78 </u> FAF _____ DIST FAF TO MAP _____ THLD _____ 4. MIN. ALT <u> RORFE/4.00 DME 2280* *2380 WITH HURON REGIONAL ALTIMETER SETTING </u> 8. MSA FROM: <u> MHE VOR/DME 3600 </u>										MAG VAR: 4E		EPOCH YEAR: 2020				
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		@						
CATEGORY =====>		A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
S-31	2280	3/4	976	2280	1	976	2280	3	976	2280	3	976				
CIRCLING	2280	1 1/4	976	2280	1 1/2	976	2280	3	976	2280	3	976				
RORFE FIX MINIMUMS																
S-31	1760	1/2	456	1760	1/2	456	1760	7/8	456	1760	1	456				
CIRCLING	1760	1	456	1760	1	456	1820	1 1/2	516	1860	2	556				
NOTES:																
CHART NOTE: VDP NA WITH HURON REGIONAL ALTIMETER SETTING. CHART NOTE: VOR MINIMUMS: INOPERATIVE TABLE DOES NOT APPLY TO S-31 CATS C AND D. CHART NOTE: RORFE FIX MINIMUMS: FOR INOPERATIVE MALSR, INCREASE S-31 CAT A VISIBILITY TO 1 3/8 MILE. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HURON REGIONAL ALTIMETER SETTING AND INCREASE ALL MDAS 100 FEET. INCREASE RORFE FIX MINIMUMS S-31 CATS C/D VISIBILITY 1/8 MILE AND CIRCLING CAT C VISIBILITY 1/4 MILE.										@ NA WHEN LOCAL WEATHER NOT AVAILABLE. @ CAT A, B 1000-2, CAT C, D 1000-3						
CITY AND STATE MITCHELL, SD		ELEVATION: 1304 AIRPORT NAME: MITCHELL MUNI		TDZE: 1304		FACILITY IDENTIFIER: MHE		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 31, AMDT 5A, 12/10/2015				SUP VOR RWY 30				
												AMDT 10 5				
												DATE 09/28/2006				